

**GLIDER EVO CLA:** Packaged air cooled liquid chillers in "A" class energy efficiency for outdoor installation, equipped with screw compressors and axial fans  
 Cooling Capacity: 284 ÷ 1513 kW



## glider evo cla rcgroupairconditioning



### MAIN FEATURES

- Air cooled liquid chiller.
- 26 models available, for a wide selection opportunity.
- Average step of 50kW.
- EER up to 3,39.
- ESEER up to 4,13.
- Twin-Screw compressors.
- R134a Refrigerant charge.
- Double refrigerant circuit.
- Shell and tube evaporator..
- AC Axial fans.
- Double air circuit.
- Electronic expansion valve.
- Suitable for outdoor installation.

### MAIN BENEFITS

- High EER, A class energy efficiency.
- Availability of kit for the reduction and the extreme reduction of the noise.
- Availability of pumping groups.
- Availability of total or partial heat recovery system.
- Availability of EC fans for a higher efficiency.
- Components dedicated to the safety of the unity.
- Eurovent Certification.

### ELECTRONIC EXPANSION VALVE

The electronic expansion valves are synonymous of an higher energy efficiency and stability of the system.

### A CLASS ENERGY EFFICIENCY

The best and most accurate components applied to the chillers.

### WORKING LIMITS IN COOLING MODE

Chilled water outlet temperature: -10÷15°C  
 Ambient temperature: -20÷45°C



## MAIN COMPONENTS

### FRAMEWORK

- Base, self supporting frame and panelling in steel plate with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders.
- Colour: RAL 9002

### COMPRESSORS

- Twin screw semi-hermetic compressors with highly efficient screw profile and high peripheral speed, optimized for R134a refrigerant.
- Integrated discharge check valve.
- Flanged-on oil separator.
- Integrated safety relief valve (overpressure inner valve).
- Replaceable cartridge oil filter.
- Valves for oil filling and discharge.
- Oil sight glass.
- Electronic protection device that includes:
  - Electric motor thermal protection via internal winding temperature sensors.
  - Phase sequence electronic relay.
  - Sensor on refrigerant discharge for temperature monitoring,
- 2-pole 3-phase electric motor with Part-Winding starting from model 290 V2 F06 to model 570 V2 F10 included.
- 2-pole 3-phase electric motor with Star / Delta starting from model 620 V2 F10 to model 1510 V2 F24 included.
- Stepless capacity control, 50÷100% for each compressor.
- Crankcase heater.
- Terminal box with IP54 enclosure class.
- Rubber supports.

### EVAPORATOR

- Single pass type shell and tube evaporator, optimized for R134a refrigerant.
- Tubes with a helical rifled internal surface.
- Intermediate baffles positioned to ensure optimum speed of the fluid and low pressure drops.
- Single circuit on water side and independent circuits, one for each compressor, on refrigerant side.
- Shell, header, tube sheets, made of carbon steel, tubes in Cu.
- Anticondensate insulation made of polyurethane.
- Temperature sensors on water inlet and outlet.
- Antifreeze heater.
- Hydraulic connections with grooved end arranged for flexible joint (the flexible joint and the adapter pipe are optional accessories).

### CONDENSING COIL

- Heat exchanger coil with high efficiency aluminium fins, specifically developed to provide high heat transfer and lower pressure drops. The combination of two factors, special tubes and fins, allow to optimally combine the following aspects:
  - Maximum capacity relative to the size of the exchanger.
  - Minimum charge of refrigerant.
  - Reduction of the air flow required for the heat exchange.
- Frame in galvanized steel.

### FANS SECTION

- Axial fans with sickle-shaped blades, fan guard and optimized for low noise levels.
- External rotor AC type electric motor with stepless variable speed for condensing pressure control, with phase-cut electronic controller.
- IP54 enclosure class.

### REFRIGERANT CIRCUIT

Component for each refrigerant circuit:

- Electronic expansion valve that allows high performance and system efficiency thanks to a timely and accurate response to changes in temperature and pressure.
- Energy reserve module for the electronic expansion valve to allow the closure of the valve in the event of lack of power supply.
- Sight glass.
- Filter dryer on liquid line.
- Service valves on liquid line.
- Service valves on compressor gas discharge.
- Double safety valve (only one in function) on high and low pressure side. The system include two safety valves with manual changeover system.
- Pressure transducers with indication, control and protection functions, on low and high refrigerant pressure and oil pressure.
- High pressure safety switch with manual reset.
- Pressure gauge on high and low pressure.
- Refrigerant circuit with copper tubing with anticondensate insulation of the suction line.
- Plastic capillary hoses for pressure sensors connection.
- R134a refrigerant charge.

### ELECTRICAL PANEL

In accordance with EN60204-1 norms, suitable for outdoor installation, complete with:

- Main switch with door lock safety.
- Fuses for each compressor.
- Magnetothermic switches for fans.
- Fuses for water pumps (if scheduled).
- Contactors for each load.
- Compressor Part-Winding starting system from model 290 V2 F06 to model 570 V2 F10 included.
- Compressor Star / Delta starting system from model 620 V2 F10 to model 1510 V2 F24 included.
- Transformer for auxiliary circuit and microprocessor supply.
- Panel with machine controls.
- Power supply 400/3/50.

### CONTROL SYSTEM

- MP.COM microprocessor system with graphic display for control and monitor of operating and alarms status. The system includes:
  - Voltage free contact for remote general alarm.
  - Main components hour-meter.
  - Nonvolatile "Flash" memory for data storage.
  - Menu with protection password.
  - LAN connection.

### HYDRAULIC CONNECTIONS OF HEAT EXCHANGERS

- Heat exchangers threaded hydraulic connections ISO 228/1 – G M, available up to a diameter of 3" included.
- Pipes threaded hydraulic connections ISO 7/1 – R, available up to a diameter of 3" included.
- The hydraulic connections with flange (FL) are not supplied with counter flange.
- The hydraulic connections with grooved end are not supplied with flexible joint (optional accessory).

## OPTIONAL ACCESSORIES

GLIDER EVO CLA SIZE	290 V2 F06	300 V2 F06	320 V2 F08	340 V2 F08	360 V2 F08	400 V2 F08	450 V2 F10	480 V2 F10	520 V2 F10	570 V2 F10	620 V2 F10
739 - Pumping group (1 pump)	●	●	●	●	●	●	●	●	●	●	●
769 - Pumping group (1+1stby)	●	●	●	●	●	●	●	●	●	●	●
740 - Pumping group (2 pumps)	-	-	-	-	-	-	-	-	-	-	-
770 - Pumping group (2+1stby)	-	-	-	-	-	-	-	-	-	-	-
1004 - Antifreezing heater for pumping group	●	●	●	●	●	●	●	●	●	●	●
118 - Kit brine A	●	●	●	●	●	●	●	●	●	●	●
119 - Kit brine B	●	●	●	●	●	●	●	●	●	●	●
79 - Electrical panel heating system	●	●	●	●	●	●	●	●	●	●	●
150 - LNO kit (noise reduction)	●	●	●	●	●	●	●	●	●	●	●
151 - ELN kit (extremely noise reduction)	●	●	●	●	●	●	●	●	●	●	●
170 - Spring antivibration holders (kit)	●	●	●	●	●	●	●	●	●	●	●
171 - Rubber antivibration holders (kit)	●	●	●	●	●	●	●	●	●	●	●
101 - EC fan	●	●	●	●	●	●	●	●	●	●	●
Evaporator flexible joint with adapter pipe (solder type)	●	●	●	●	●	●	●	●	●	●	●
Evaporator flexible joint with adapter for flange connection	●	●	●	●	●	●	●	●	●	●	●
450 - Desuperheater	●	●	●	●	●	●	●	●	●	●	●
449 - Voltage free contact for partial heat recovery water pump activation	●	●	●	●	●	●	●	●	●	●	●
451 - 100% heat recovery	●	●	●	●	●	●	●	●	●	●	●
454 - Voltage free contact for total heat recovery water pump activation	●	●	●	●	●	●	●	●	●	●	●
Selection switch for operation mode for total heat recovery	●	●	●	●	●	●	●	●	●	●	●
Total heat recovery flexible joint with adapter pipe (solder type)	●	●	●	●	●	●	●	●	●	●	●
Total heat recovery flexible joint with adapter for flange connection	-	-	-	-	-	-	-	-	-	-	-
351 - Coils with pre-painted fins	-	-	-	-	-	-	-	-	-	-	-
Condensing coil in special execution	●	●	●	●	●	●	●	●	●	●	●
250 - Coils protection nets (kit)	●	●	●	●	●	●	●	●	●	●	●
731 - Safety water flow switch	●	●	●	●	●	●	●	●	●	●	●
Analog flowmeter	●	●	●	●	●	●	●	●	●	●	●
650 - Compressor thermal relay	●	●	●	●	●	●	●	●	●	●	●
605 - Compr. power factor capacitor - 0,9	●	●	●	●	●	●	●	●	●	●	●
Supply network control relay	●	●	●	●	●	●	●	●	●	●	●
83 - Compressor operation indicator	●	●	●	●	●	●	●	●	●	●	●
550 - Stop valve on compressor suction line	●	●	●	●	●	●	●	●	●	●	●
1005 - Oil flow switch	●	●	●	●	●	●	●	●	●	●	●
85 - Demand limit	●	●	●	●	●	●	●	●	●	●	●
88 - Analog set point compensation	●	●	●	●	●	●	●	●	●	●	●
919 - Clock card	●	●	●	●	●	●	●	●	●	●	●
923 - RC-Com MBUS/JBUS Serial board	●	●	●	●	●	●	●	●	●	●	●
926 - LON Serial board	●	●	●	●	●	●	●	●	●	●	●
931 - BACnet Ethernet - SNMP - TCP/IP Serial board	●	●	●	●	●	●	●	●	●	●	●
932 - BACnet MS/TP Serial board	●	●	●	●	●	●	●	●	●	●	●
934 - MP.COM expansion card	●	●	●	●	●	●	●	●	●	●	●
942 - Serial card for GSM Modem	●	●	●	●	●	●	●	●	●	●	●
943 - Data Logger	●	●	●	●	●	●	●	●	●	●	●
Ambient temperature sensor	●	●	●	●	●	●	●	●	●	●	●
889 - Master plant SEQUENCER	●	●	●	●	●	●	●	●	●	●	●
962 - Kit modem GSM	●	●	●	●	●	●	●	●	●	●	●
957 - Plantwatch without modem	●	●	●	●	●	●	●	●	●	●	●
930 - Remote graphic terminal kit	●	●	●	●	●	●	●	●	●	●	●

● available accessory; - not available accessory

## OPTIONAL ACCESSORIES

GLIDER EVO CLA SIZE	660 V2 F12	700 V2 F12	760 V2 F14	830 V2 F14	870 V2 F14	920 V2 F14	980 V2 F16	1020 V2 F16	1090 V2 F18	1150 V2 F20	1280 V2 F20
739 - Pumping group (1 pump)	●	●	-	-	-	-	-	-	-	-	-
769 - Pumping group (1+1stby)	●	●	-	-	-	-	-	-	-	-	-
740 - Pumping group (2 pumps)	-	-	●	●	●	●	●	●	●	●	●
770 - Pumping group (2+1stby)	-	-	●	●	●	●	●	●	●	●	●
1004 - Antifreezing heater for pumping group	●	●	●	●	●	●	●	●	●	●	●
118 - Kit brine A	●	●	●	●	●	●	●	●	●	●	●
119 - Kit brine B	●	●	●	●	●	●	●	●	●	●	●
79 - Electrical panel heating system	●	●	●	●	●	●	●	●	●	●	●
150 - LNO kit (noise reduction)	●	●	●	●	●	●	●	●	●	●	●
151 - ELN kit (extremely noise reduction)	●	●	●	●	●	●	●	●	●	●	●
170 - Spring antivibration holders (kit)	●	●	●	●	●	●	●	●	●	●	●
171 - Rubber antivibration holders (kit)	●	●	●	●	●	●	●	●	●	●	●
101 - EC fan	●	●	●	●	●	●	●	●	●	●	●
Evaporator flexible joint with adapter pipe (solder type)	●	●	●	●	●	●	●	●	●	●	●
Evaporator flexible joint with adapter for flange connection	●	●	●	●	●	●	●	●	●	●	●
450 - Desuperheater	●	●	●	●	●	●	●	●	●	●	●
449 - Voltage free contact for partial heat recovery water pump activation	●	●	●	●	●	●	●	●	●	●	●
451 - 100% heat recovery	●	●	●	●	●	●	●	●	●	●	●
454 - Voltage free contact for total heat recovery water pump activation	●	●	●	●	●	●	●	●	●	●	●
Selection switch for operation mode for total heat recovery	●	●	●	●	●	●	●	●	●	●	●
Total heat recovery flexible joint with adapter pipe (solder type)	●	●	●	●	●	●	●	●	●	●	●
Total heat recovery flexible joint with adapter for flange connection	-	-	-	-	-	-	-	-	-	-	-
351 - Coils with pre-painted fins	-	-	-	-	-	-	-	-	-	-	-
Condensing coil in special execution	●	●	●	●	●	●	●	●	●	●	●
250 - Coils protection nets (kit)	●	●	●	●	●	●	●	●	●	●	●
731 - Safety water flow switch	●	●	●	●	●	●	●	●	●	●	●
Analog flowmeter	●	●	●	●	●	●	●	●	●	●	●
650 - Compressor thermal relay	●	●	●	●	●	●	●	●	●	●	●
605 - Compr. power factor capacitor - 0,9	●	●	●	●	●	●	●	●	●	●	●
Supply network control relay	●	●	●	●	●	●	●	●	●	●	●
83 - Compressor operation indicator	●	●	●	●	●	●	●	●	●	●	●
550 - Stop valve on compressor suction line	●	●	●	●	●	●	●	●	●	●	●
1005 - Oil flow switch	●	●	●	●	●	●	●	●	●	●	●
85 - Demand limit	●	●	●	●	●	●	●	●	●	●	●
88 - Analog set point compensation	●	●	●	●	●	●	●	●	●	●	●
919 - Clock card	●	●	●	●	●	●	●	●	●	●	●
923 - RC-Com MBUS/JBUS Serial board	●	●	●	●	●	●	●	●	●	●	●
926 - LON Serial board	●	●	●	●	●	●	●	●	●	●	●
931 - BACnet Ethernet - SNMP - TCP/IP Serial board	●	●	●	●	●	●	●	●	●	●	●
932 - BACnet MS/TP Serial board	●	●	●	●	●	●	●	●	●	●	●
934 - MP.COM expansion card	●	●	●	●	●	●	●	●	●	●	●
942 - Serial card for GSM Modem	●	●	●	●	●	●	●	●	●	●	●
943 - Data Logger	●	●	●	●	●	●	●	●	●	●	●
Ambient temperature sensor	●	●	●	●	●	●	●	●	●	●	●
889 - Master plant SEQUENCER	●	●	●	●	●	●	●	●	●	●	●
962 - Kit modem GSM	●	●	●	●	●	●	●	●	●	●	●
957 - Plantwatch without modem	●	●	●	●	●	●	●	●	●	●	●
930 - Remote graphic terminal kit	●	●	●	●	●	●	●	●	●	●	●

● available accessory; - not available accessory

## OPTIONAL ACCESSORIES

GLIDER EVO CLA SIZE	1350 V2 F20	1430 V2 F20	1470 V2 F22	1510 V2 F24
739 - Pumping group (1 pump)	-	-	-	-
769 - Pumping group (1+1stby)	-	-	-	-
740 - Pumping group (2 pumps)	●	●	●	●
770 - Pumping group (2+1stby)	●	●	●	●
1004 - Antifreezing heater for pumping group	●	●	●	●
118 - Kit brine A	●	●	●	●
119 - Kit brine B	●	●	●	●
79 - Electrical panel heating system	●	●	●	●
150 - LNO kit (noise reduction)	●	●	●	●
151 - ELN kit (extremely noise reduction)	●	●	●	●
170 - Spring antivibration holders (kit)	●	●	●	●
171 - Rubber antivibration holders (kit)	●	●	●	●
101 - EC fan	●	●	●	●
Evaporator flexible joint with adapter pipe (solder type)	●	●	●	●
Evaporator flexible joint with adapter for flange connection	●	●	●	●
450 - Desuperheater	●	●	●	●
449 - Voltage free contact for partial heat recovery water pump activation	●	●	●	●
451 - 100% heat recovery	●	●	●	●
454 - Voltage free contact for total heat recovery water pump activation	●	●	●	●
Selection switch for operation mode for total heat recovery	●	●	●	●
Total heat recovery flexible joint with adapter pipe (solder type)	●	●	●	●
Total heat recovery flexible joint with adapter for flange connection	-	-	-	●
351 - Coils with pre-painted fins	-	-	-	●
Condensing coil in special execution	●	●	●	●
250 - Coils protection nets (kit)	●	●	●	●
731 - Safety water flow switch	●	●	●	●
Analog flowmeter	●	●	●	●
650 - Compressor thermal relay	●	●	●	●
605 - Compr. power factor capacitor - 0,9	●	●	●	●
Supply network control relay	●	●	●	●
83 - Compressor operation indicator	●	●	●	●
550 - Stop valve on compressor suction line	●	●	●	●
1005 - Oil flow switch	●	●	●	●
85 - Demand limit	●	●	●	●
88 - Analog set point compensation	●	●	●	●
919 - Clock card	●	●	●	●
923 - RC-Com MBUS/JBUS Serial board	●	●	●	●
926 - LON Serial board	●	●	●	●
931 - BACnet Ethernet - SNMP - TCP/IP Serial board	●	●	●	●
932 - BACnet MS/TP Serial board	●	●	●	●
934 - MP.COM expansion card	●	●	●	●
942 - Serial card for GSM Modem	●	●	●	●
943 - Data Logger	●	●	●	●
Ambient temperature sensor	●	●	●	●
889 - Master plant SEQUENCER	●	●	●	●
962 - Kit modem GSM	●	●	●	●
957 - Plantwatch without modem	●	●	●	●
930 - Remote graphic terminal kit	●	●	●	●

● available accessory; - not available accessory

## TECHNICAL DATA GLIDER EVO

		290 V2 F06	300 V2 F06	320 V2 F08	340 V2 F08	360 V2 F08	400 V2 F08	450 V2 F10	480 V2 F10
<b>GLIDER EVO CLA SIZE</b>		<b>284</b>	<b>300</b>	<b>320</b>	<b>340</b>	<b>358</b>	<b>399</b>	<b>446</b>	<b>472</b>
<b>Cooling capacity (1)</b>	kW	88,8	95,2	100,9	107,9	113,3	125,9	142,0	149,4
Unit power input	kW	48,8	51,5	54,9	58,5	61,5	68,5	76,6	81,1
Evaporator water flow rate	m³/h	30	17	19	21	17	13	17	17
Evaporator pressure drop	kPa								
Compressors		twin-screw							
Quantity	n.	2	2	2	2	2	2	2	2
Capacity control	%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%
Axial fans	n.	6	6	7	8	8	8	10	10
Total air flow	m³/h	131388	127614	153286	175184	170152	170152	212690	212690
Air circuits	n.	2	2	2	2	2	2	2	2
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a
Total refrigerant charge (optional excluded)	kg	74	74	96	96	96	145	120	181
Gas circuits	n.	2	2	2	2	2	2	2	2
Power supply	V/Ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
Max unit operating current (FLA)	A	186,8	202,6	217,8	233,0	236,2	266,8	308,6	327,2
Unit starting current (LRA)	A	374,1	380,0	419,9	435,1	413,7	500,0	668,8	678,1
EER (1)	kW/kW	3,20	3,15	3,17	3,15	3,16	3,17	3,14	3,16
ESEER		3,26	3,76	4,13	4,13	4,06	3,79	3,73	3,77
Sound power level [Lw] (2)	dB(A)	92,0	92,5	92,7	92,9	91,5	91,9	92,1	96,2
Average sound pressure level [Lpm] (3)	dB(A)	72,3	72,8	72,5	72,7	71,3	71,7	71,4	75,5
Net weight	kg	3738	4109	4515	4520	4697	4902	5428	5662
Hydraulic connections									
Evaporator IN/OUT - OD (4)	Ø mm	141,3	141,3	141,3	141,3	168,3	168,3	168,3	168,3
Partial heat recovery (5)									
<b>Heating capacity</b>	kW	<b>56,4</b>	<b>59,7</b>	<b>65,6</b>	<b>67,7</b>	<b>72,9</b>	<b>79,4</b>	<b>88,8</b>	<b>93,9</b>
Total heat recovery (6)									
<b>Heating capacity</b>	kW	<b>348</b>	<b>380</b>	<b>404</b>	<b>428</b>	<b>453</b>	<b>507</b>	<b>565</b>	<b>598</b>
Pumping group - Power input	kW	5,5	5,5	5,5	5,5	5,5	5,5	5,5	5,5
<b>LNO KIT 100%</b>									
<b>Cooling capacity (1)</b>	kW	<b>284</b>	<b>300</b>	<b>320</b>	<b>340</b>	<b>358</b>	<b>399</b>	<b>446</b>	<b>472</b>
Unit power input	kW	88,8	95,2	100,9	107,9	113,3	125,9	142,0	149,4
Total air flow	m³/h	131388	127614	153286	175184	170152	170152	212690	212690
EER (1)	kW/kW	3,20	3,15	3,17	3,15	3,16	3,17	3,14	3,16
Sound power level [Lw] (2)	dB(A)	90,0	90,5	90,7	90,9	89,5	89,9	90,1	94,2
Average sound pressure level [Lpm] (3)	dB(A)	70,3	70,8	70,5	70,7	69,3	69,7	69,4	73,5
<b>LNO KIT 85%</b>									
<b>Cooling capacity (1)</b>	kW	<b>279</b>	<b>296</b>	<b>316</b>	<b>337</b>	<b>355</b>	<b>395</b>	<b>442</b>	<b>468</b>
Unit power input	kW	88,6	96,4	101,3	107,7	113,8	127,4	142,1	150,0
Total air flow	m³/h	111680	108472	130293	148906	144629	144629	180787	180787
EER (1)	kW/kW	3,15	3,07	3,12	3,13	3,12	3,10	3,11	3,12
Sound power level [Lw] (2)	dB(A)	89,0	89,5	89,7	89,9	88,5	88,9	89,1	93,2
Average sound pressure level [Lpm] (3)	dB(A)	69,3	69,8	69,5	69,7	68,3	68,7	68,4	72,5
<b>LNO KIT 70%</b>									
<b>Cooling capacity (1)</b>	kW	<b>273</b>	<b>290</b>	<b>311</b>	<b>332</b>	<b>350</b>	<b>388</b>	<b>436</b>	<b>461</b>
Unit power input	kW	88,9	99,0	103,0	108,9	115,1	130,2	143,9	152,1
Total air flow	m³/h	91972	89330	107300	122629	119106	119106	148883	148883
EER (1)	kW/kW	3,07	2,93	3,02	3,05	3,04	2,98	3,03	3,03
Sound power level [Lw] (2)	dB(A)	86,0	86,5	86,7	86,9	85,5	85,9	86,1	90,2
Average sound pressure level [Lpm] (3)	dB(A)	66,3	66,8	66,5	66,7	65,3	65,7	65,4	69,5
<b>ELN KIT</b>									
<b>Cooling capacity (1)</b>	kW	<b>273</b>	<b>290</b>	<b>311</b>	<b>332</b>	<b>350</b>	<b>388</b>	<b>436</b>	<b>461</b>
Unit power input	kW	88,9	99,0	103,0	108,9	115,1	130,2	143,9	152,1
Total air flow	m³/h	91972	89330	107300	122629	119106	119106	148883	148883
EER (1)	kW/kW	3,07	2,93	3,02	3,05	3,04	2,98	3,03	3,03
Sound power level [Lw] (2)	dB(A)	83,0	83,5	83,7	83,9	82,5	82,9	83,1	87,2
Average sound pressure level [Lpm] (3)	dB(A)	63,3	63,8	63,5	63,7	62,3	62,7	62,4	66,5

1. Referred to chilled water temperature 12/7°C and 35°C ambient air temperature according to Eurovent standard
2. Sound power level [Lw] according to ISO EN 9614 – 2.
3. Average sound pressure level [Lpm] 1m far according to ISO EN 3744.
4. Hydraulic connection with grooved end. The flexible joint is an optional accessory.
5. Referred to chiller water temperature 12/7°C; 35°C ambient air temperature; hot water temperature 40/45°C.
6. Referred to chiller water temperature 12/7°C; hot water temperature 40/45°C.

## TECHNICAL DATA GLIDER EVO

GLIDER EVO CLA SIZE		520 V2 F10	570 V2 F10	620 V2 F10	660 V2 F12	700 V2 F12	760 V2 F14	830 V2 F14	870 V2 F14	
STANDARD	<b>Cooling capacity (1)</b>	kW	<b>518</b>	<b>566</b>	<b>615</b>	<b>656</b>	<b>696</b>	<b>762</b>	<b>828</b>	<b>873</b>
	Unit power input	kW	164,4	179,7	192,8	205,6	220,3	240,4	261,2	277,1
	Evaporator water flow rate	m³/h	89	97,1	106	113	120	131	142	150
	Evaporator pressure drop	kPa	17	24	49	33	38	44	51	56
	Compressors		twin-screw							
	Quantity	n.	2	2	2	2	2	2	2	
	Capacity control	%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	
	Axial fans	n.	10	10	10	11	12	13	14	
	Total air flow	m³/h	212690	212690	212690	244303	262776	284674	306572	
	Air circuits	n.	2	2	2	2	2	2	2	
OPTIONAL	Refrigerant		R134a							
	Total refrigerant charge (optional excluded)	kg	181	181	181	217	217	252	252	
	Gas circuits	n.	2	2	2	2	2	2	2	
	Power supply	V/Ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	
	Max unit operating current (FLA)	A	348,3	369,4	405,8	433,3	460,8	494,8	528,8	
	Unit starting current (LRA)	A	829,1	850,2	583,4	610,9	614,8	648,8	665,7	
	EER (1)	kW/kW	3,15	3,15	3,19	3,19	3,16	3,17	3,15	
	ESEER		3,76	3,77	3,76	3,82	3,76	3,74	3,72	
	Sound power level [Lw] (2)	dB(A)	96,4	96,7	96,7	99,3	100,4	101,1	101,6	
	Average sound pressure level [Lpm] (3)	dB(A)	75,8	76,0	76,0	78,2	79,4	79,7	80,3	
LNO KIT 100%	Net weight	kg	5999	6121	6112	6733	6743	7404	8139	
	Hydraulic connections									
	Evaporator IN/OUT - OD (4)	Ø mm	168,3	168,3	168,3	219,1	219,1	219,1	219,1	
	Partial heat recovery (5)									
	<b>Heating capacity</b>	kW	<b>103,0</b>	<b>112,0</b>	<b>122,0</b>	<b>130,0</b>	<b>138,0</b>	<b>151,0</b>	<b>164,0</b>	
	Total heat recovery (6)									
	<b>Heating capacity</b>	kW	<b>659</b>	<b>720</b>	<b>782</b>	<b>836</b>	<b>887</b>	<b>971</b>	<b>1053</b>	
	Pumping group - Power input	kW	5,5	5,5	5,5	5,5	5,5	11,0	11,0	
	<b>Cooling capacity (1)</b>	kW	<b>518</b>	<b>566</b>	<b>615</b>	<b>656</b>	<b>696</b>	<b>762</b>	<b>828</b>	
	Unit power input	kW	164,4	179,7	192,8	205,6	220,3	240,4	261,2	
LNO KIT 85%	Total air flow	m³/h	212690	212690	212690	244303	262776	284674	306572	
	EER (1)	kW/kW	3,15	3,15	3,19	3,19	3,16	3,17	3,15	
	Sound power level [Lw] (2)	dB(A)	94,4	94,7	94,7	97,3	98,4	99,1	99,6	
	Average sound pressure level [Lpm] (3)	dB(A)	73,8	74,0	74,0	76,2	77,4	77,7	78,3	
	<b>Cooling capacity (1)</b>	kW	<b>513</b>	<b>557</b>	<b>606</b>	<b>645</b>	<b>686</b>	<b>751</b>	<b>815</b>	
	Unit power input	kW	165,0	181,4	196,1	209,4	222,7	244,6	264,6	
	Total air flow	m³/h	180787	180787	180787	207658	223360	241973	260586	
	EER (1)	kW/kW	3,11	3,07	3,09	3,08	3,08	3,07	3,08	
	Sound power level [Lw] (2)	dB(A)	93,4	93,7	93,7	96,3	97,4	98,1	98,7	
	Average sound pressure level [Lpm] (3)	dB(A)	72,8	73,0	73,0	75,2	76,4	76,7	77,3	
LNO KIT 70%	<b>Cooling capacity (1)</b>	kW	<b>506</b>	<b>545</b>	<b>591</b>	<b>629</b>	<b>670</b>	<b>733</b>	<b>796</b>	
	Unit power input	kW	168,1	186,6	201,7	214,7	228,7	250,2	271,7	
	Total air flow	m³/h	148883	148883	148883	171012	183943	199272	214600	
	EER (1)	kW/kW	3,01	2,92	2,93	2,93	2,93	2,93	2,88	
	Sound power level [Lw] (2)	dB(A)	90,4	90,7	90,7	93,3	94,4	95,1	95,6	
	Average sound pressure level [Lpm] (3)	dB(A)	69,8	70,0	70,0	72,2	73,4	73,7	74,1	
	<b>Cooling capacity (1)</b>	kW	<b>506</b>	<b>545</b>	<b>591</b>	<b>629</b>	<b>670</b>	<b>733</b>	<b>796</b>	
	Unit power input	kW	168,1	186,6	201,7	214,7	228,7	250,2	271,7	
	Total air flow	m³/h	148883	148883	148883	171012	183943	199272	214600	
	EER (1)	kW/kW	3,01	2,92	2,93	2,93	2,93	2,93	2,88	
ELN KIT	Sound power level [Lw] (2)	dB(A)	87,4	87,7	87,7	90,3	91,4	92,1	92,7	
	Average sound pressure level [Lpm] (3)	dB(A)	66,8	67,0	67,0	69,2	70,4	70,7	71,3	
	<b>Cooling capacity (1)</b>	kW	<b>506</b>	<b>545</b>	<b>591</b>	<b>629</b>	<b>670</b>	<b>733</b>	<b>796</b>	
	Unit power input	kW	168,1	186,6	201,7	214,7	228,7	250,2	271,7	
	Total air flow	m³/h	148883	148883	148883	171012	183943	199272	214600	
	EER (1)	kW/kW	3,01	2,92	2,93	2,93	2,93	2,93	2,88	
	Sound power level [Lw] (2)	dB(A)	87,4	87,7	87,7	90,3	91,4	92,1	92,6	
	Average sound pressure level [Lpm] (3)	dB(A)	66,8	67,0	67,0	69,2	70,4	70,7	71,1	

1. Referred to chilled water temperature 12/7°C and 35°C ambient air temperature according to Eurovent standard

2. Sound power level [Lw] according to ISO EN 9614 – 2.

3. Average sound pressure level [Lpm] 1m far according to ISO EN 3744.

4. Hydraulic connection with grooved end. The flexible joint is an optional accessory.

5. Referred to chiller water temperature 12/7°C; 35°C ambient air temperature; hot water temperature 40/45°C.

6. Referred to chiller water temperature 12/7°C; hot water temperature 40/45°C.

## TECHNICAL DATA GLIDER EVO

GLIDER EVO CLA SIZE		920 V2 F14	980 V2 F16	1020 V2 F16	1090 V2 F18	1150 V2 F20	1280 V2 F20	1350 V2 F20	1430 V2 F20	
<b>STANDARD</b>	<b>Cooling capacity (1)</b>	kW	<b>919</b>	<b>977</b>	<b>1024</b>	<b>1083</b>	<b>1154</b>	<b>1279</b>	<b>1355</b>	<b>1433</b>
	Unit power input	kW	290,8	306,3	320,0	341,6	364,0	398,4	426,1	452,1
	Evaporator water flow rate	m³/h	158	168	176	186	198	220	233	246
	Evaporator pressure drop	kPa	61	68	76	71	79	54	41	44
	Compressors		twin-screw	twin-screw	twin-screw	twin-screw	twin-screw	twin-screw	twin-screw	
	Quantity	n.	2	2	2	2	2	2	2	
	Capacity control	%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	25... 100%	
	Axial fans	n.	14	16	16	18	20	20	20	
	Total air flow	m³/h	297766	350368	350368	401014	451660	437960	431670	425380
	Air circuits	n.	2	2	2	2	2	2	2	
<b>OPTIONAL</b>	Refrigerant		R134a	R134a	R134a	R134a	R134a	R134a	R134a	
	Total refrigerant charge (optional excluded)	kg	337	290	290	326	362	362	412	462
	Gas circuits	n.	2	2	2	2	2	2	2	
	Power supply	V/Ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	
	Max unit operating current (FLA)	A	590,4	629,8	677,8	732,7	787,6	875,6	924,8	974
	Unit starting current (LRA)	A	775,5	889,1	965,1	1080,9	1135,8	1259,8	1352,8	1402
	EER (1)	kW/kW	3,16	3,19	3,20	3,17	3,17	3,21	3,18	3,17
	ESEER		3,71	3,72	3,74	3,74	3,72	3,80	3,83	3,81
	Sound power level [Lw] (2)	dB(A)	101,4	99,9	99,9	101,7	103,9	103,9	104,1	104,2
	Average sound pressure level [Lpm] (3)	dB(A)	80,0	78,1	78,1	79,5	81,5	81,5	81,7	81,8
<b>LNO KIT 100%</b>	Net weight	kg	8544	9195	9318	10274	11180	11362	11972	12292
	Hydraulic connections									
	Evaporator IN/OUT - OD (4)	Ø mm	219,1	219,1	273	273	273	323,9	323,9	
	Partial heat recovery (5)									
	<b>Heating capacity</b>	kW	<b>182,0</b>	<b>194,0</b>	<b>203,0</b>	<b>216,0</b>	<b>228,0</b>	<b>254,0</b>	<b>269,0</b>	<b>285,0</b>
	Total heat recovery (6)									
	<b>Heating capacity</b>	kW	<b>1176</b>	<b>1244</b>	<b>1306</b>	<b>1386</b>	<b>1466</b>	<b>1630</b>	<b>1735</b>	<b>1843</b>
	Pumping group - Power input	kW	11,0	11,0	11,0	11,0	11,0	11,0	11,0	11,0
	<b>Cooling capacity (1)</b>	kW	<b>919</b>	<b>977</b>	<b>1024</b>	<b>1083</b>	<b>1154</b>	<b>1279</b>	<b>1355</b>	<b>1433</b>
	Unit power input	kW	290,8	306,3	320,0	341,6	364,0	398,4	426,1	452,1
<b>LNO KIT 85%</b>	Total air flow	m³/h	297766	350368	350368	401014	451660	437960	431670	425380
	EER (1)	kW/kW	3,16	3,19	3,2	3,17	3,17	3,21	3,18	3,17
	Sound power level [Lw] (2)	dB(A)	99,4	97,9	97,9	99,7	101,9	101,9	102,1	102,2
	Average sound pressure level [Lpm] (3)	dB(A)	78,0	76,1	76,1	77,5	79,5	79,5	79,7	79,8
	<b>Cooling capacity (1)</b>	kW	<b>903</b>	<b>962</b>	<b>1008</b>	<b>1066</b>	<b>1136</b>	<b>1257</b>	<b>1330</b>	<b>1405</b>
	Unit power input	kW	297,0	311,3	325,2	346,1	367,6	405,5	434,6	462,2
	Total air flow	m³/h	253101	297813	297813	340862	383911	372266	366920	361573
	EER (1)	kW/kW	3,04	3,09	3,10	3,08	3,09	3,10	3,06	3,04
	Sound power level [Lw] (2)	dB(A)	98,4	96,9	96,9	98,7	100,9	100,9	101,1	101,2
	Average sound pressure level [Lpm] (3)	dB(A)	77,0	75,1	75,1	76,5	78,5	78,5	78,7	78,8
<b>LNO KIT 70%</b>	<b>Cooling capacity (1)</b>	kW	<b>879</b>	<b>940</b>	<b>985</b>	<b>1040</b>	<b>1109</b>	<b>1225</b>	<b>1292</b>	<b>1363</b>
	Unit power input	kW	307,3	319,7	336,2	356,2	377,2	418,1	450,2	481,6
	Total air flow	m³/h	208436	245258	245258	280710	316162	306572	302169	297766
	EER (1)	kW/kW	2,86	2,94	2,93	2,92	2,94	2,93	2,87	2,83
	Sound power level [Lw] (2)	dB(A)	95,4	93,9	93,9	95,7	97,9	97,9	98,1	98,2
	Average sound pressure level [Lpm] (3)	dB(A)	74,0	72,1	72,1	73,5	75,5	75,5	75,7	75,8
	<b>Cooling capacity (1)</b>	kW	<b>879</b>	<b>940</b>	<b>985</b>	<b>1040</b>	<b>1109</b>	<b>1225</b>	<b>1292</b>	<b>1363</b>
	Unit power input	kW	307,3	319,7	336,2	356,2	377,2	418,1	450,2	481,6
	Total air flow	m³/h	208436	245258	245258	280710	316162	306572	302169	297766
	EER (1)	kW/kW	2,86	2,94	2,93	2,92	2,94	2,93	2,87	2,83
<b>ELN KIT</b>	Sound power level [Lw] (2)	dB(A)	92,4	90,9	90,9	92,7	94,9	94,9	95,1	95,2
	Average sound pressure level [Lpm] (3)	dB(A)	71,0	69,1	69,1	70,5	72,5	72,5	72,7	72,8

1. Referred to chilled water temperature 12/7°C and 35°C ambient air temperature according to Eurovent standard
2. Sound power level [Lw] according to ISO EN 9614 – 2.
3. Average sound pressure level [L<sub>pm</sub>] 1m far according to ISO EN 3744.
4. Hydraulic connection with grooved end. The flexible joint is an optional accessory.
5. Referred to chiller water temperature 12/7°C; 35°C ambient air temperature; hot water temperature 40/45°C.
6. Referred to chiller water temperature 12/7°C; hot water temperature 40/45°C.

## TECHNICAL DATA GLIDER EVO

	GLIDER EVO CLA SIZE	1470 V2 F22	1510 V2 F24
<b>Cooling capacity (1)</b>	<b>kW</b>	<b>1471</b>	<b>1513</b>
Unit power input	kW	449,8	446,3
Evaporator water flow rate	m³/h	253	260
Evaporator pressure drop	kPa	35	35
Compressors		twin-screw	twin-screw
Quantity	n.	2	2
Capacity control	%	25... 100%	25... 100%
Axial fans	n.	22	24
Total air flow	m³/h	467918	510456
Air circuits	n.	2	2
Refrigerant		R134a	R134a
Total refrigerant charge (optional excluded)	kg	530	578
Gas circuits	n.	2	2
Power supply	V/Ph/Hz	400/3/50	400/3/50
Max unit operating current (FLA)	A	981,8	989,6
Unit starting current (LRA)	A	1409,8	1417,6
EER (1)	kW/kW	3,27	3,39
ESEER		3,92	4,03
Sound power level [Lw] (2)	dB(A)	104,2	104,2
Average sound pressure level [Lpm] (3)	dB(A)	81,6	81,3
Net weight	kg	12931	13090
Hydraulic connections			
Evaporator IN/OUT - OD (4)	Ø mm	323,9	323,9
Partial heat recovery (5)			
<b>Heating capacity</b>	<b>kW</b>	<b>292,0</b>	<b>301,0</b>
Total heat recovery (6)			
<b>Heating capacity</b>	<b>kW</b>	<b>1869</b>	<b>1896</b>
Pumping group - Power input	kW	11,0	11,0
<b>Cooling capacity (1)</b>	<b>kW</b>	<b>1471</b>	<b>1513</b>
Unit power input	kW	449,8	446,3
Total air flow	m³/h	467918	510456
EER (1)	kW/kW	3,27	3,39
Sound power level [Lw] (2)	dB(A)	102,2	102,2
Average sound pressure level [Lpm] (3)	dB(A)	79,6	79,3
<b>Cooling capacity (1)</b>	<b>kW</b>	<b>1444</b>	<b>1488</b>
Unit power input	kW	458,4	453,7
Total air flow	m³/h	397730	433888
EER (1)	kW/kW	3,15	3,28
Sound power level [Lw] (2)	dB(A)	101,2	101,2
Average sound pressure level [Lpm] (3)	dB(A)	78,6	78,3
<b>Cooling capacity (1)</b>	<b>kW</b>	<b>1404</b>	<b>1452</b>
Unit power input	kW	474,3	465,4
Total air flow	m³/h	327543	357319
EER (1)	kW/kW	2,96	3,12
Sound power level [Lw] (2)	dB(A)	98,2	98,2
Average sound pressure level [Lpm] (3)	dB(A)	75,6	75,3
<b>Cooling capacity (1)</b>	<b>kW</b>	<b>1404</b>	<b>1452</b>
Unit power input	kW	474,3	465,4
Total air flow	m³/h	327543	357319
EER (1)	kW/kW	2,96	3,12
Sound power level [Lw] (2)	dB(A)	95,2	95,2
Average sound pressure level [Lpm] (3)	dB(A)	72,6	72,3

1. Referred to chilled water temperature 12/7°C and 35°C ambient air temperature according to Eurovent standard
2. Sound power level [Lw] according to ISO EN 9614 – 2.
3. Average sound pressure level [Lpm] 1m far according to ISO EN 3744.
4. Hydraulic connection with grooved end. The flexible joint is an optional accessory.
5. Referred to chiller water temperature 12/7°C; 35°C ambient air temperature; hot water temperature 40/45°C.
6. Referred to chiller water temperature 12/7°C; hot water temperature 40/45°C.

## DIMENSIONS (mm)

## SIZE F

	a	b	c
F06	3520	2260	2550
F08	4490	2260	2550
F10	5460	2260	2550
F12	6430	2260	2550
F14	7400	2260	2550
F16	8720	2260	2550
F18	9690	2260	2550
F20	10660	2260	2550
F22	11630	2260	2550
F24	12600	2260	2550

