

Climaveneta Technical Documentation
WSM2-Y_0264_0604_202005_ML

REGULATION (EU) N. 2016/2281 FOR ROOFTOP HEAT PUMPS

Ecodesign requirements for space heaters

REVERSIBLE AIR COOLED ROOFTOP UNIT

WSM2-Y 0264 - 0604

Heating Capacity Range 81,1 - 182 [kW] - (EN14511 VALUE)
Nominal Heating Capacity at TdesignH Range 82,0 - 184 [kW]



1. REGULATION (EU) N. 2016/2281 FOR ROOFTOP HEAT PUMPS

1.1 Scope of the document	3
1.2 REGULATION (UE) N. 2016/2281 description	3
1.3 Description of the data declared by Mitsubishi Electric Hydronics & IT Cooling Systems	3

2. CLIMAVENETA CONTENTS UNIT

2.1 Table index	4
-----------------	---

3. TECHNICAL PARAMETERS

3.1 WSM2-Y /	5
--------------	---



1. REGULATION (EU) N. 2016/2281 FOR ROOFTOP HEAT PUMPS

1.1 Scope of the document

This document is compliant with the Commission Regulation (EU) N. 2016/2281 regarding "REQUIREMENTS FOR PRODUCT INFORMATION" (Annex II, Point 5). In particular, it deals with rooftop heat pumps and contains information required by Table 14 of the above-mentioned regulation, which is entitled "Information requirements for heat pumps".

1.2 REGULATION (EU) N. 2016/2281 description

The COMMISSION REGULATION (EU) N. 2016/2281 of 30 November 2016, implementing Directive 2009/125/EC of the European Parliament and of the Council, establishes eco-design requirements for the placing on the market and/or putting into service of: air heating products with a rated heating capacity which does not exceed 1MW, cooling products and high temperature process chillers with a rated cooling capacity which do not exceed 2 MW, and all fan coil units. All these energy-related products are defined in Article 2 of the Regulation in question.

1.3 Description of the data declared by Mitsubishi Electric Hydronics & IT Cooling Systems

- Rooftop heat pumps: an air-to-air or water/brine-to-air heat pump driven by an electric compressor, with evaporator, compressor and condenser integrated into a single package.
- T_{designH}: temperature at reference design conditions.
- Design heating load (P_{designh}): the heating load applied to a heat pump at the reference design temperature whereby the design heating load is equal to the part load for heating with outdoor temperature equal to reference design temperature for heating, expressed in kW.
- Seasonal space heating energy efficiency ($\eta_{s,h}$): ratio between the space heating demand pertaining to the designated heating season, and the annual energy consumption required to meet this demand, expressed in %.
- Seasonal Coefficient Of Performance (SCOP): the overall energy efficiency ratio of the rooftop heat pump, representative for the heating season, calculated as the reference annual heating demand divided by the annual energy consumption for heating.
- Bivalent temperature: the outdoor temperature declared by the manufacturer at which the declared capacity for heating equals the part load for heating and below which the declared heating capacity requires a supplementary back-up heater capacity to meet the part load for heating, expressed in degrees Celsius.
- Operation limit temperature: the outdoor temperature declared by the manufacturer for heating, below which the heat pump will not be able to deliver any heating capacity, and the declared heating capacity is equal to zero, expressed in degrees Celsius.
- Degradation coefficient: measure of efficiency loss due to cycling of the rooftop.
- Off mode: a condition in which the rooftop is connected to the mains power source and is not providing any function.
- Thermostat off-mode: condition corresponding to the hours with no heating load and activated heating function, whereby the heating function is switched on but the rooftop is not operational.
- Crankcase heater mode: condition in which a heating device is activated to avoid the refrigerant migrating to the compressor so as to limit the refrigerant concentration in oil when the compressor is started.
- Standby mode: condition where the rooftop is connected to the mains power source and depends on energy input from the mains power source to work as intended. The unit provides only the following functions, which may persist for an indefinite time: reactivation function, or reactivation function and only an indication of enabled reactivation function, and/or information or status display.
- Supplementary capacity for heating: rated supplemental heat output provided by a supplementary heater when the heating load exceeds the heating capacity of the rooftop heat pump, expressed in kW.
- Capacity control: the ability of a rooftop to change its heating capacity by changing the volumetric flow rate of at least one of the fluids needed to operate the refrigeration cycle.
- Sound power level (LWA): the A-weighted sound power level, indoors and/or outdoors, expressed in dB.
- Annual electricity consumption for heating: the energy consumption required to meet the reference annual heating demand.
- Global warming potential (GWP) of the refrigerant: the 100-year climatic warming potential of one kilogram of a greenhouse gas relative to one kilogram of dioxide (CO₂).

2. CLIMAVENETA CONTENTS UNIT

2.1 Table index

REVERSIBLE AIR COOLED ROOFTOP UNIT

WSM2-Y 0264 - 0604

Heating Capacity Range 81,1 - 182 [kW]

Nominal Heating Capacity at TdesignH Range 82,0 - 184 [kW]

Units	Version	Size					Pag.
WSM2-Y		0264	0304	0354	0404	0444	5
		0484	0524	0604			

WSM2-Y 0264			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	82
Seasonal space heating energy efficiency	η_s	[%]	133,8
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	53,2
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	34,7
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	24,4
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	27,9
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	54,5
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	47,3
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,68
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,83
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	3,74
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,11
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,71
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,50
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,111
Standby mode	PSB	[kW]	0,090
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	17,1
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	83
Annual electricity consumption for heating	QHE	[kWh]	26335
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	41240
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0304			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	92
Seasonal space heating energy efficiency	η_s	[%]	141,8
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	60,5
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	39,4
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	25,7
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	29,3
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	61,8
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	53,9
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,81
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,75
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,31
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,72
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,86
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,61
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,126
Standby mode	PSB	[kW]	0,090
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	19,2
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	83
Annual electricity consumption for heating	QHE	[kWh]	28303
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	39350
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0354			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	104
Seasonal space heating energy efficiency	η_s	[%]	140,6
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	68,4
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	44,5
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	29,3
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	33,3
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	70,0
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	61,0
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,61
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,79
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,31
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,74
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,65
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,42
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,168
Standby mode	PSB	[kW]	0,090
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	21,7
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	84
Annual electricity consumption for heating	QHE	[kWh]	32288
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	39350
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0404			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	122
Seasonal space heating energy efficiency	η_s	[%]	143,4
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	79,9
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	52,1
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	34,1
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	38,8
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	81,8
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	71,2
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,64
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,88
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,02
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,41
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,68
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,45
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,200
Standby mode	PSB	[kW]	0,090
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	25,5
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	84
Annual electricity consumption for heating	QHE	[kWh]	37035
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	37580
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0444			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	132
Seasonal space heating energy efficiency	η_s	[%]	144,2
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	86,2
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	56,1
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	36,1
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	40,5
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	88,2
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	76,7
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,56
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,99
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,36
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	5,10
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,60
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,37
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,247
Standby mode	PSB	[kW]	0,170
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	27,6
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	90
Annual electricity consumption for heating	QHE	[kWh]	39687
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	60880
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0484			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	139
Seasonal space heating energy efficiency	η_s	[%]	138,6
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	90,7
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	59,1
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	40,2
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	46,0
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	92,9
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	80,6
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,42
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,85
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,31
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,78
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,46
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,24
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,375
Standby mode	PSB	[kW]	0,170
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	29,2
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	91
Annual electricity consumption for heating	QHE	[kWh]	43434
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	73260
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0524			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	159
Seasonal space heating energy efficiency	η_s	[%]	140,2
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	104
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	67,5
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	44,6
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	51,3
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	106
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	92,1
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,52
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,91
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,24
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,70
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,55
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,33
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,453
Standby mode	PSB	[kW]	0,170
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	33,2
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	92
Annual electricity consumption for heating	QHE	[kWh]	48994
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	77824
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

WSM2-Y 0604			
Air-to-air heat pump	yes / no		yes
Water-to-air heat pump	yes / no		no
Brine-to-air heat pump	yes / no		no
With supplementary heater:	yes / no		no
Air flow rate	fixed / variable		fixed
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Nominal heating capacity	Prated	[kW]	184
Seasonal space heating energy efficiency	η_s	[%]	139,0
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	119
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	77,7
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	52,6
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	60,2
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	122
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	106
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-6,0
Degradation coefficient	Cdh	-	0,25
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	2,54
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	3,88
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	4,16
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	4,63
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	2,58
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	2,36
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-10
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,572
Standby mode	PSB	[kW]	0,170
Crankcase heater mode	PCK	[kW]	0,000
Supplementary heater			
Back-up heating capacity	Psup	[kW]	38,5
Type of energy input			electric
Other items			
Capacity control	fixed/variable/staged		Staged
Sound power level, outdoors	LWA	[dB(A)]	92
Annual electricity consumption for heating	QHE	[kWh]	56853
GWP of the refrigerant		[Kg CO2eq]	2088
Outdoor heat exchanger			
For air-to-air HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	73260
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	-

Unit in standard configuration/execution, without optional accessories.

Contact details: Mitsubishi Electric Hydronics & IT Cooling Systems S.p.A., via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

ENGLISH	ITALIANO	FRANCAISE	DEUTSCH	ESPAÑOL
Air-to-air heat pump	Pompa di calore aria/aria	Pompe à chaleur air-air	Luft-Luft-Wärmepumpe	Bomba de calor aire-aire
Water-to-air heat pump	Pompa di calore acqua/aria	Pompe à chaleur eau-air	Wasser-Luft-Wärmepumpe	Bomba de calor agua-aire
Brine-to-air heat pump	Pompa di calore salamoia/aria	Pompe à chaleur eau glycolée-air	Sole-Luft-Wärmepumpe	Bomba de calor salmuera-aire
With supplementary heater:	Con riscaldatore supplementare:	Equipée d'un dispositif de chauffage d'appoint:	Mit Zusatzheizgerät:	Equipado con un calefactor complementario:
Air flow rate	Portata Aria	Débit d'air	Luftdurchsatz	Caudal de aire
Parameters are declared for average/warmer/colder climate conditions	I parametri sono dichiarati per condizioni climatiche medie/ alte/ basse	Les paramètres sont déclarés pour les conditions climatiques moyennes/chaud/basse	Die Parameter sind für eine Mitteltemperaturanwendung anzugeben	Los parámetros se indicarán para condiciones climáticas medias/ alta/ baja
Nominal heating capacity	Potenza termica nominale	Puissance thermique nominale	Heizleistung nominal	Potencia térmica nominal
Seasonal space heating energy efficiency	Efficienza energetica stagionale del riscaldamento d'ambiente	Efficacité énergétique saisonnière pour le chauffage des locaux	Jahreszeitbedingte Raumheizungs-Energieeffizienz	Eficiencia energética estacional de calefacción
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj	Capacità di riscaldamento dichiarata a carico parziale, con temperatura interna pari a 20 °C e temperatura esterna Tj	Puissance calorifique déclarée à charge partielle pour une température intérieure de 20 °C et une température extérieure Tj	Angegebene Leistung für Teillast bei Raumlufttemperatur 20 °C und Außenlufttemperatur Tj	Capacidad de calefacción declarada para una carga parcial a una temperatura interior de 20 °C y una temperatura exterior Tj
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Capacità di riscaldamento con temperatura esterna Tj = - 7 °C	Puissance calorifique déclarée avec la température extérieure Tj = - 7 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = - 7 °C	Capacidad de calefacción para una temperatura exterior Tj = - 7 °C
Declared capacity for heating with outdoor temperature Tj = +2 °C	Capacità di riscaldamento con temperatura esterna Tj = + 2 °C	Puissance calorifique déclarée avec la température extérieure Tj = +2 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = +2 °C	Capacidad de calefacción para una temperatura exterior Tj = +2 °C
Declared capacity for heating with outdoor temperature Tj = +7 °C	Capacità di riscaldamento con temperatura esterna Tj = + 7 °C	Puissance calorifique déclarée avec la température extérieure Tj = +7 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = +7 °C	Capacidad de calefacción para una temperatura exterior Tj = +7 °C
Declared capacity for heating with outdoor temperature Tj = +12 °C	Capacità di riscaldamento con temperatura esterna Tj = + 12 °C	Puissance calorifique déclarée avec la température extérieure Tj = +12 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = +12 °C	Capacidad de calefacción para una temperatura exterior Tj = +12 °C
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Capacità di riscaldamento con temperatura esterna Tj = temperatura bivalente	Puissance calorifique déclarée avec la température extérieure Tj = Température bivalente	Erklärt, Raumheizung mit Außenlufttemperatur Tj = Bivalenttemperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura bivalente
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Capacità di riscaldamento con temperatura esterna Tj = temperatura limite di esercizio	Puissance calorifique déclarée avec la température extérieure Tj = Température maximale de service	Erklärt, Raumheizung mit Außenlufttemperatur Tj = Betriebsgrenzwert-Temperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura límite de funcionamiento
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Per le pompe di calore aria/acqua: Tj = - 15 °C (se TOL < - 20 °C)	Pour les pompes à chaleur air-eau: Tj = - 15 °C (si TOL < - 20 °C)	Für Luft-Wasser-Wärmepumpen: Tj = - 15 °C (wenn TOL < - 20 °C)	Para bombas de calor aire-agua: Tj = - 15 °C (si TOL < - 20 °C)
Bivalent temperature	Temperatura bivalente	Température bivalente	Bivalenttemperatur	Temperatura bivalente
Degradation coefficient	Coefficiente di degradazione	Coefficient de dégradation	Minderungsfaktor	Coefficiente de degradación
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj	Coefficiente di prestazione dichiarato o indice di energia primaria per carico parziale, con temperatura interna pari a 20 °C e temperatura esterna Tj	Coefficient de performance déclaré ou coefficient sur énergie primaire déclaré à charge partielle pour une température intérieure de 20 °C et une température extérieure Tj	Angegebene Leistungszahl oder Heizzahl für Teillast bei Raumlufttemperatur 20 °C und Außenlufttemperatur Tj	Coefficiente de rendimiento declarado o factor energético primario para una carga parcial a una temperatura interior de 20 °C y una temperatura exterior Tj
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	Coefficiente di prestazione con temperatura esterna Tj = - 7 °C	Coefficient de performance déclaré avec la température extérieure Tj = - 7 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = - 7 °C	Capacidad de calefacción para una temperatura exterior Tj = - 7 °C
Declared coefficient of performance with outdoor temperature Tj = +2 °C	Coefficiente di prestazione con temperatura esterna Tj = + 2 °C	Coefficient de performance déclaré avec la température extérieure Tj = +2 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = +2 °C	Capacidad de calefacción para una temperatura exterior Tj = +2 °C
Declared coefficient of performance with outdoor temperature Tj = +7 °C	Coefficiente di prestazione con temperatura esterna Tj = + 7 °C	Coefficient de performance déclaré avec la température extérieure Tj = +7 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = +7 °C	Capacidad de calefacción para una temperatura exterior Tj = +7 °C
Declared coefficient of performance with outdoor temperature Tj = +12 °C	Coefficiente di prestazione con temperatura esterna Tj = + 12 °C	Coefficient de performance déclaré avec la température extérieure Tj = +12 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = +12 °C	Capacidad de calefacción para una temperatura exterior Tj = +12 °C
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	Coefficiente di prestazione con temperatura esterna Tj = temperatura bivalente	Coefficient de performance déclaré avec la température extérieure Tj = Température bivalente	Erklärten Leistungszahl bei Außenlufttemperatur Tj = Bivalenttemperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura bivalente
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	Coefficiente di prestazione con temperatura esterna Tj = temperatura limite di esercizio	Coefficient de performance déclaré avec la température extérieure Tj = Température maximale de service	Erklärten Leistungszahl bei Außenlufttemperatur Tj = Betriebsgrenzwert-Temperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura límite de funcionamiento
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Per le pompe di calore aria/acqua: Tj = - 15 °C (se TOL < - 20 °C)	Pour les pompes à chaleur air-eau: Tj = - 15 °C (si TOL < - 20 °C)	Für Luft-Wasser-Wärmepumpen: Tj = - 15 °C (wenn TOL < - 20 °C)	Para bombas de calor aire-agua: Tj = - 15 °C (si TOL < - 20 °C)

ENGLISH	ITALIANO	FRANCAISE	DEUTSCH	ESPAÑOL
For air-to-water HP : Operation	Per le pompe di calore aria/	Pour les pompes à chaleur	Für Luft-Wasser-Wärmepumpen:	Para bombas de calor aire-agua:
Power consumption in modes other than active mode	Consumo energetico in modi diversi dal modo attivo	Consommation d'électricité dans les modes autres que le mode actif	Stromverbrauch in anderen Betriebsarten als dem Betriebszustand	Consumo de electricidad en modos distintos del activo
Off mode	Modo spento	Mode arrêt	Aus-Zustand	Modo desactivado
Thermostat-off mode	Modo termostato spento	Mode arrêt par thermostat	Thermostat-aus-Zustand	Modo desactivado por termostato
Standby mode	Modo stand-by	Mode veille	Bereitschaftszustand	Modo de espera
Crankcase heater mode	Modo riscaldamento del carter	Mode résistance de carter active	Betriebszustand mit Kurbelgehäuseheizung	Modo riscaldamento del carter
Supplementary heater	Riscaldatore supplementare	Dispositif de chauffage d'appoint	Zusatzheizgerät	Calefactor complementario
Back-up heating capacity	Potenza termica backup	Puissance calorifique du dispositif de chauffage d'appoint	Reserveheizleistung	Potencia de calefacción de reserva
Type of energy input	Tipo di input energia	Type d'énergie utilisée	Art der Energiezufuhr	Tipo de energía consumida
Other items	Altri elementi	Autres caractéristiques	Sonstige Elemente	Otros elementos
Capacity control	Controllo della capacità	Régulation de la puissance	Leistungssteuerung	Control de capacidad
Sound power level, outdoors	Livello della potenza sonora, all'esterno	Niveau de puissance acoustique, à l'extérieur	Schalleistungspegel, außen	Nivel de potencia acústica (exterior)
Annual electricity consumption for heating	Consumo di elettricità annuale per il riscaldamento	Consommation annuelle d'électricité pour le chauffage	Jahresstromverbrauch für die Heizung	Consumo anual de electricidad para la calefacción
GWP of the refrigerant	GWP del refrigerante	PRP du fluide frigorigène	Treibhausgaspotenzial des Kältemittels	PCA del refrigerante
Outdoor heat exchanger	Scambiatore di calore esterno	Echangeur de chaleur côté extérieur	Wärmetauscher außen	Intercambiador de calor de exterior
For air-to-air HP: Rated air flow rate, outdoors	Per le pompe di calore aria/aria: portata d'aria, all'esterno	Pour les pompes à chaleur air-air: débit d'air, mesuré à l'extérieur	Für Luft-Luft- Wärmepumpen: Luftdurchsatz, außen gemessen	Bombas de calor aire- aire: caudal de aire (exterior)
For water-/brine-to-air heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Per le pompe di calore acqua/aria e salamoia/aria: flusso di salamoia o acqua nominale, scambiatore di calore all'esterno	Pour les pompes à chaleur eau/eau glycolée-air: débit nominal d'eau glycolée ou d'eau, échangeur de chaleur côté extérieur	Für Wasser/Sole-Luft-Wärmepumpen: Wasser- oder Sole- Nenndurchsatz, Wärmetauscher außen	Para bombas de calor agua-aire/salmuera- aire: caudal nominal de salmuera o agua, intercambiador de calor de exterior
Notes:	Note:	Remarques:	Hinweise:	Notas:
The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.	I parametri sono dichiarati per l'applicazione a temperatura media, tranne per le pompe di calore a bassa temperatura. Per le pompe di calore a bassa temperatura, i parametri sono dichiarati per l'applicazione a bassa temperatura.	Les paramètres sont déclarés pour l'application à moyenne température, excepté pour les pompes à chaleur basse température. Pour les pompes à chaleur basse température, les paramètres sont déclarés pour l'application à basse température.	Die Parameter sind für eine Mitteltemperaturanwendung anzugeben, außer für Niedertemperatur-Wärmepumpen. Für Niedertemperatur-Wärmepumpen sind die Parameter für eine Niedertemperaturanwendung anzugeben.	Los parámetros se declararán para aplicaciones de media temperatura, excepto si se trata de bombas de calor de baja temperatura. En el caso de las bombas de calor de baja temperatura, los parámetros se declararán para aplicaciones de baja temperatura.
Unit in standard configuration/execution, without optional accessories.	Unità in configurazione ed esecuzione standard, priva di accessori opzionali.	Unité en configuration et exécution standard, sans accessoires optionnels.	Gerät mit Standard-Konfiguration und -Ausführung, ohne wunschweises Zubehör.	Unidad en configuración y ejecución estándar, sin accesorios opcionales.



for a greener tomorrow

Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.



mitsubishi electric hydronics & it cooling systems S.p.A.

Head Office: Via Caduti di Cefalonia 1 - 36061 Bassano del Grappa (VI) - Italy

Tel (+39) 0424 509 500 - Fax (+39) 0424 509 509

www.climaveneta.com

www.melcohit.com