

Climaveneta Technical Documentation
NX-W_/H_0122_1204_201801_ML

REGULATION (EU) N. 813/2013

Ecodesign requirements for space heaters

Water to water heat pumps, reversible on hydraulic side

NX-W /H 0122 - 1204

Heating Capacity Range 40,1 - 292 [kW] - (EN14511 VALUE)
Nominal Heating Capacity at TdesignH Range 46,0 - 335 [kW]



NX-W-H 0122 - 0802



NX-W-H 0604 - 1204



1. REGULATION (EU) N. 813/2013	
1.1 Scope of the document	3
1.2 REGULATION (EU) N. 813/2013 description	3
1.3 Description of the data declared by Mitsubishi Electric Hydronics & IT Cooling Systems	3
2. CLIMAVENETA CONTENTS UNIT	
2.1 Table index	4
3. TECHNICAL PARAMETERS	
3.1 NX-W /	5



1. REGULATION (EU) N. 813/2013

1.1 Scope of the document

This document is compliant with the Commission Regulation (EU) N. 813/2013 regarding "REQUIREMENTS FOR PRODUCT INFORMATION" (Annex II, Point 5) and it is made by the required information set out of the Table 2, Annex II of the Regulation called "Information requirements for heat pump space heaters and heat pump combination heaters".

1.2 REGULATION (EU) N. 813/2013 description

The COMMISSION REGULATION (EU) N. 813/2013 of 2 August 2013, implementing Directive 2009/125/EC of the European Parliament and of the Council, establishes ecodesign requirements for the placing on the market and/or putting into service of space heaters and combination heaters with a rated heat output ≤ 400 kW, including those integrated in packages of space heater, temperature control and solar device or packages of combination heater, temperature control and solar device as defined in Article 2 of Commission Delegated Regulation (EU) N. 811/2013.

1.3 Description of the data declared by Mitsubishi Electric Hydronics & IT Cooling Systems

- Heat pump combination heater: heat pump space heater that is designed to also provide heat to deliver hot drinking.
- Low-temperature application: application where the heat pump space heater delivers its declared capacity for heating at an indoor heat exchanger outlet temperature of 35 °C.
- Medium-temperature application: application where the heat pump space heater or heat pump combination heater delivers its declared capacity for heating at an indoor heat exchanger outlet temperature of 55 °C.
- TdesignH: temperature at reference design conditions.
- PdesignH , Design load for heating: the rated heat output of a heat pump space heater or heat pump combination heater at the reference design temperature, whereby the design load for heating is equal to the part load for heating with outdoor temperature equal to reference design temperature, expressed in kW.
- Seasonal space heating energy efficiency (η_s): ratio between the space heating demand for a designated heating season, supplied by a heater and the annual energy consumption required to meet this demand, expressed in %.
- Seasonal space heating energy efficiency class: efficiency class determined on the basis of its seasonal space heating energy efficiency with a difference distribution between heaters and low temperature heat pumps.
- Low-temperature heat pump: heat pump space heater that is specifically designed for low-temperature application, and that cannot deliver heating water with an outlet temperature of 52 °C at an inlet dry (wet) bulb temperature of - 7 °C (- 8 °C) in the reference design conditions for average climate.
- Bivalent temperature: the outdoor temperature declared by the manufacturer for heating at which the declared capacity for heating equals the part load for heating and below which the declared capacity for heating requires supplementary capacity for heating to meet the part load for heating.
- Operation limit temperature: the outdoor temperature declared by the manufacturer for heating, below which the air-to-water heat pump space heater or air-to-water heat pump combination heater will not be able to deliver any heating capacity and the declared capacity for heating is equal to zero.
- Degradation coefficient: measure of efficiency loss due to cycling of heat pump space heaters or heat pump combination heaters.
- Off mode: a condition in which the heat pump space heater or heat pump combination heater is connected to the mains power source and is not providing any function.
- Thermostat-off mode: condition corresponding to the hours with no heating load and activated heating function, whereby the heating function is switched on but the heat pump space heater or heat pump combination heater is not operational.
- Standby mode: condition where the heater is connected to the mains power source, depends on energy input from the mains power source to work as intended and provides only the following functions, which may persist for an indefinite time: reactivation function, or reactivation function and only an indication of enabled reactivation function, and/or information or status display.
- Crankcase heater mode: condition in which a heating device is activated to avoid the refrigerant migrating to the compressor so as to limit the refrigerant concentration in oil when the compressor is started.
- Seasonal coefficient of performance (SCOP): the overall coefficient of performance of a heat pump heater representative of the designated heating season, calculated as the reference annual heating demand divided by the annual energy consumption.
- Supplementary capacity for heating: rated heat output of a supplementary heater that supplements the declared capacity for heating to meet the part

load for heating, if the declared capacity for heating is less than the part load for heating.

- Capacity control: ability of a heat pump space heater or heat pump combination heater to change its capacity by changing the volumetric flow rate of at least one of the fluids needed to operate the refrigeration cycle.
- Annual energy consumption: means the energy consumption required to meet the reference annual heating demand for a designated heating season.
- Sound power level (LWA): the A-weighted sound power level, indoors and/or outdoors, expressed in dB.

2. CLIMAVENETA CONTENTS UNIT

2.1 Table index

Water to water heat pumps, reversible on hydraulic side

NX-W /H 0122 - 1204

Heating Capacity Range 40,1 - 292 [kW]

Nominal Heating Capacity at TdesignH Range 46,0 - 335 [kW]

Units	Version	Size					Pag.
NX-W		0122	0152	0182	0202	0252	5
		0262	0302	0352	0402	0452	
		0502	0552	0602	0604	0702	
		0704	0802	0804	0904		

NX-W /H /0122 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	51
Seasonal space heating energy efficiency	ηs	[%]	228
Seasonal space heating energy efficiency class	-	-	A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	45,1
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	27,5
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	24,4
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	24,8
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	45,1
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	44,9
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,67
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,06
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,42
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,84
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,67
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,53
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,597
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	6,09
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	74
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	17894
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	11

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0122 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	46
Seasonal space heating energy efficiency	ηs	[%]	177
Seasonal space heating energy efficiency class	-	-	A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	40,7
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	24,8
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	22,9
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	23,6
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	40,7
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	40,1
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,63
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,70
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,49
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,36
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,63
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,34
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,315
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	5,91
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	74
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	20600
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	8

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0152 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	64
Seasonal space heating energy efficiency	ηs	[%]	232
Seasonal space heating energy efficiency class	-	-	A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	56,4
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	34,3
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	30,6
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	31,0
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	56,4
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	56,2
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,68
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,14
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,58
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	7,07
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,68
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,55
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,810
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	7,55
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	74
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	21985
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	14

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0152 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	57
Seasonal space heating energy efficiency	ηs	[%]	179
Seasonal space heating energy efficiency class	-	-	A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	50,9
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	31,0
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	28,7
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	29,6
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	50,9
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	50,1
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,73
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,75
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,52
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,47
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,73
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,47
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,437
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	7,43
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	74
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	25381
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	11

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0182 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	76
Seasonal space heating energy efficiency	ηs	[%]	227
Seasonal space heating energy efficiency class	-	-	A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	66,8
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	40,7
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	36,1
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	36,6
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	66,8
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	66,5
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,79
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,04
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,32
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,67
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,79
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,66
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,943
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	9,02
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	75
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	26600
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	16

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0182 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	68
Seasonal space heating energy efficiency	ηs	[%]	181
Seasonal space heating energy efficiency class	-	-	A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	60,0
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	36,5
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	33,9
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	34,9
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	60,0
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	59,1
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,83
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,54
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,33
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,52
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,502
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	8,72
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	75
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	29609
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	13

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0202 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	87
Seasonal space heating energy efficiency	ηs	[%]	233
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	77,2
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	47,0
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	41,9
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	42,6
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	77,2
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	76,8
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,78
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,21
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,52
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,91
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,78
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,67
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,949
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	10,5
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	75
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	29960
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	19

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0202 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	79
Seasonal space heating energy efficiency	ηs	[%]	183
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	70,0
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	42,6
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	39,3
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	40,6
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	70,0
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	69,2
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,87
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,63
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,47
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,55
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,508
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,140
Supplementary heater			
Nominal heating capacity	Psup	[kW]	9,93
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	75
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	34174
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	15

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0252 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	97
Seasonal space heating energy efficiency	ηs	[%]	238
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	85,7
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	52,2
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	46,8
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	47,7
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	85,7
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	85,3
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,89
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,32
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,69
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	7,15
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,89
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,75
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,046
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,134
Supplementary heater			
Nominal heating capacity	Psup	[kW]	11,6
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	75
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	32604
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	21

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0252 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	87
Seasonal space heating energy efficiency	ηs	[%]	184
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	76,9
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	46,8
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	43,7
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	45,2
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	76,9
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	75,8
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,76
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,88
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,70
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,63
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,76
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,47
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,531
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,134
Supplementary heater			
Nominal heating capacity	Psup	[kW]	11,1
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	75
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	37443
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	16

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0262 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	110
Seasonal space heating energy efficiency	ηs	[%]	235
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	97,2
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	59,2
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	52,8
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	53,6
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	97,2
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	96,7
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,81
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,25
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,60
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,99
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,81
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,68
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,034
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,134
Supplementary heater			
Nominal heating capacity	Psup	[kW]	13,2
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	76
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	37425
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	23

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0262 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	99
Seasonal space heating energy efficiency	ηs	[%]	184
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	87,2
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	53,1
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	49,5
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	51,1
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	87,2
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	85,7
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,80
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,90
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,66
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,49
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,80
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,50
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,547
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,134
Supplementary heater			
Nominal heating capacity	Psup	[kW]	12,9
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	76
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	42459
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	18

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0302 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	129
Seasonal space heating energy efficiency	ηs	[%]	236
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	114
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	69,6
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	62,1
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	63,0
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	114
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	114
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,78
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,25
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,66
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	7,11
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,78
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,64
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,188
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,134
Supplementary heater			
Nominal heating capacity	Psup	[kW]	15,5
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	77
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	43852
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	27

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0302 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	116
Seasonal space heating energy efficiency	ηs	[%]	184
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	103
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	62,4
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	58,3
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	60,1
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	103
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	101
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,90
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,63
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,50
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,55
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,636
Standby mode	PSB	[kW]	0,023
Crankcase heater mode	PCK	[kW]	0,134
Supplementary heater			
Nominal heating capacity	Psup	[kW]	15,1
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	77
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	49901
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	21

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0352 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	149
Seasonal space heating energy efficiency	ηs	[%]	238
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	132
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	80,2
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	62,9
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	63,9
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	132
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	131
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,80
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,29
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,67
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	7,13
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,80
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,67
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,315
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,150
Supplementary heater			
Nominal heating capacity	Psup	[kW]	17,9
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	78
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	49928
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	32

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0352 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	133
Seasonal space heating energy efficiency	ηs	[%]	186
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	118
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	71,8
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	59,0
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	61,0
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	118
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	116
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,91
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,68
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,56
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,82
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,54
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,701
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,150
Supplementary heater			
Nominal heating capacity	Psup	[kW]	17,3
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	78
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	56808
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	25

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0402 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	169
Seasonal space heating energy efficiency	ηs	[%]	235
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	149
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	90,8
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	81,6
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	83,1
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	149
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	148
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,81
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,24
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,65
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	7,00
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,81
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,69
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,472
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,166
Supplementary heater			
Nominal heating capacity	Psup	[kW]	20,3
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	78
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	57368
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	36

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0402 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	150
Seasonal space heating energy efficiency	ηs	[%]	184
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	133
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	81,0
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	76,0
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	78,8
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	133
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	131
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,81
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,92
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,69
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,53
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,81
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,53
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,766
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,166
Supplementary heater			
Nominal heating capacity	Psup	[kW]	19,4
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	78
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	64625
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	28

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0452 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	190
Seasonal space heating energy efficiency	ηs	[%]	236
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	168
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	102
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	82,6
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	84,1
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	168
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	167
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,79
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,24
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,63
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,97
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,79
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,67
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,656
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,185
Supplementary heater			
Nominal heating capacity	Psup	[kW]	22,8
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	79
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	64268
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	40

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0452 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	170
Seasonal space heating energy efficiency	ηs	[%]	186
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	150
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	91,4
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	76,9
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	79,8
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	150
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	148
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,81
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,92
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,72
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,57
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,81
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,52
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,851
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,185
Supplementary heater			
Nominal heating capacity	Psup	[kW]	22,0
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	79
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	72366
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	31

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0502 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	211
Seasonal space heating energy efficiency	ηs	[%]	232
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	186
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	113
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	101
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	103
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	186
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	186
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,76
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,19
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,55
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,92
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,76
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,64
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,874
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	25,2
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	79
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	72424
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	45

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0502 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	189
Seasonal space heating energy efficiency	ηs	[%]	184
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	167
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	102
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	95,0
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	98,1
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	167
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	165
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,80
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,91
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,64
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,48
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,80
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,52
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,945
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	24,5
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	79
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	81390
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	35

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0552 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	242
Seasonal space heating energy efficiency	ηs	[%]	236
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	214
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	130
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	103
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	104
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	214
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	213
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,81
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,26
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,53
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,90
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,81
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,68
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	2,119
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	29,0
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	80
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	81971
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	51

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0552 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	217
Seasonal space heating energy efficiency	ηs	[%]	187
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	192
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	117
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	96,2
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	99,4
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	192
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	188
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,83
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,94
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,71
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,52
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,83
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,55
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,046
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	28,2
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	80
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	91820
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	40

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0602 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	273
Seasonal space heating energy efficiency	ηs	[%]	236
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	242
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	147
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	132
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	134
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	242
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	240
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,83
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,29
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,64
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	7,03
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,83
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,69
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	2,430
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	32,7
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	80
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	92359
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	58

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0602 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	244
Seasonal space heating energy efficiency	ηs	[%]	186
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	216
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	131
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	123
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	128
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	216
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	212
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,84
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,96
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,75
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,59
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,84
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,56
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,151
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	31,7
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	80
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	103746
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	45

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0604 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	255
Seasonal space heating energy efficiency	ηs	[%]	239
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	226
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	137
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	88,3
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	64,7
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	226
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	225
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,73
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,29
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,53
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,71
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,73
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,59
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,679
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,268
Supplementary heater			
Nominal heating capacity	Psup	[kW]	30,4
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	87
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	85269
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	54

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0604 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	229
Seasonal space heating energy efficiency	ηs	[%]	184
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	203
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	123
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	79,3
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	61,8
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	203
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	199
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,76
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,81
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,50
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,32
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,76
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,49
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,852
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,268
Supplementary heater			
Nominal heating capacity	Psup	[kW]	29,7
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	87
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	98397
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	42

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0702 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	308
Seasonal space heating energy efficiency	ηs	[%]	235
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	273
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	166
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	133
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	135
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	273
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	271
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,75
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,22
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,56
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,91
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,75
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,62
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	3,032
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	36,9
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	83
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	104855
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	65

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0702 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	277
Seasonal space heating energy efficiency	ηs	[%]	188
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	245
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	149
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	124
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	129
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	245
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	241
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,86
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,96
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,77
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,57
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,86
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,58
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,493
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	35,8
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	83
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	116667
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	51

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0704 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	294
Seasonal space heating energy efficiency	ηs	[%]	239
Seasonal space heating energy efficiency class	-	-	
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	260
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	158
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	102
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	65,2
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	260
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	259
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,74
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,27
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,50
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,59
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,74
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,60
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,970
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,300
Supplementary heater			
Nominal heating capacity	Psup	[kW]	35,2
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	88
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	98458
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	62

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0704 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	263
Seasonal space heating energy efficiency	ηs	[%]	185
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	233
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	142
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	91,2
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	62,4
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	233
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	229
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,75
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,82
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,53
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,31
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,75
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,48
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	0,969
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,300
Supplementary heater			
Nominal heating capacity	Psup	[kW]	34,1
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	88
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	112639
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	48

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0802 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	339
Seasonal space heating energy efficiency	ηs	[%]	225
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	300
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	182
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	165
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	167
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	300
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	298
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,62
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,01
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,31
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,64
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,62
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,50
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	3,176
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	40,5
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	84
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	120091
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	65

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0802 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	308
Seasonal space heating energy efficiency	ηs	[%]	181
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	272
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	166
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	155
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	160
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	272
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	268
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,80
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,83
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,50
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,23
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,80
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,53
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,932
Standby mode	PSB	[kW]	0,033
Crankcase heater mode	PCK	[kW]	0,204
Supplementary heater			
Nominal heating capacity	Psup	[kW]	39,6
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	84
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	134739
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	57

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0804 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	332
Seasonal space heating energy efficiency	ηs	[%]	239
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	294
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	179
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	115
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	85,0
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	294
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	293
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,74
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,30
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,50
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,66
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,74
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,60
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	2,363
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,332
Supplementary heater			
Nominal heating capacity	Psup	[kW]	40,0
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	89
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	111335
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	70

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0804 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	297
Seasonal space heating energy efficiency	ηs	[%]	188
Seasonal space heating energy efficiency class	-	-	
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	263
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	160
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	103
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	80,8
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	263
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	259
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,74
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,90
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,69
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,45
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,74
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,46
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,126
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,332
Supplementary heater			
Nominal heating capacity	Psup	[kW]	38,2
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	89
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	125328
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	54

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0904 LOW TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		low 35°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	371
Seasonal space heating energy efficiency	ηs	[%]	243
Seasonal space heating energy efficiency class	-	-	
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	328
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	200
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	128
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	85,4
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	328
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	326
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	5,74
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	6,38
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	6,68
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,75
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	5,74
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	5,60
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	2,263
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,370
Supplementary heater			
Nominal heating capacity	Psup	[kW]	44,4
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	90
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	122136
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	71

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

NX-W /H /0904 MEDIUM TEMPERATURE application			
Air-to-water heat pump:	yes / no		no
Water-to-water heat pump:	yes / no		yes
Brine-to-water heat pump:	yes / no		no
Low-temperature heat pump:	yes / no		no
With supplementary heater:	yes / no		no
Mixed unit with heat pump:	yes / no		no
Temperature application (1)	(low 35°C/ medium 55°C)		medium 55°C
Water flow rate	fixed / variable		fixed
Outlet temperature	fixed / variable		variable
Parameters are declared for average/warmer/colder climate conditions (1)	average / warmer / colder		average
Rated heat output at Tdesignh	Prated = Pdesignh	[kW]	335
Seasonal space heating energy efficiency	ηs	[%]	189
Seasonal space heating energy efficiency class	-	-	-
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Pdh	[kW]	297
Declared capacity for heating with outdoor temperature Tj = +2 °C	Pdh	[kW]	180
Declared capacity for heating with outdoor temperature Tj = +7 °C	Pdh	[kW]	116
Declared capacity for heating with outdoor temperature Tj = +12 °C	Pdh	[kW]	81,3
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Pdh	[kW]	297
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Pdh	[kW]	292
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	[kW]	-
Bivalent temperature	Tbiv	[°C]	-7
Degradation coefficient	Cdh	-	0,90
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	COPd	-	3,75
Declared coefficient of performance with outdoor temperature Tj = +2 °C	COPd	-	4,92
Declared coefficient of performance with outdoor temperature Tj = +7 °C	COPd	-	5,73
Declared coefficient of performance with outdoor temperature Tj = +12 °C	COPd	-	6,46
Declared coefficient of performance with outdoor temperature Tj = Bivalent temperature	COPd	-	3,75
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	COPd	-	3,47
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
For air-to-water HP : Operation limit temperature	TOL	[°C]	-
Heating water operating limit temperature	WTOL	[°C]	60
Power consumption in modes other than active mode			
Off mode	POFF	[kW]	0,000
Thermostat-off mode	PTO	[kW]	1,292
Standby mode	PSB	[kW]	0,043
Crankcase heater mode	PCK	[kW]	0,370
Supplementary heater			
Nominal heating capacity	Psup	[kW]	43,3
Other items			
Capacity control	fixed / variable		variable
Sound power level, indoors	LWA	[dB(A)]	90
Sound power level, outdoors	LWA	[dB(A)]	-
Annual electricity consumption for heating	QHE	[kWh]	140544
Outdoor heat exchanger			
For air-to-water HP: Rated air flow rate, outdoors	Qairsorce	[m³/h]	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Qwater/brine source	[m³/h]	61

(1) The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.

Unit in standard configuration/execution, without optional accessories.

ENGLISH	ITALIANO	FRANCAISE	DEUTSCH	ESPAÑOL
Air-to-water heat pump:	Pompa di calore aria/ acqua:	Pompes à chaleur air-eau:	Luft-Wasser-Wärmepumpe:	Bomba de calor aire-agua:
Water-to-water heat pump:	Pompa di calore acqua/ acqua:	Pompes à chaleur eau-eau:	Wasser-Wasser-Wärmepumpe:	Bomba de calor agua-agua:
Brine-to-water heat pump:	Pompa di calore salamoia/ acqua:	Pompe à chaleur eau glycolée-eau:	Sole-Wasser-Wärmepumpe:	Bomba de calor salmuera-agua:
Low-temperature heat pump:	Pompa di calore a bassa temperatura:	Pompes à chaleur basse température:	Niedertemperatur-Wärmepumpe:	Bomba de calor de baja temperatura:
With supplementary heater:	Con riscaldatore supplementare:	Equipée d'un dispositif de chauffage d'appoint:	Mit Zusatzheizgerät:	Equipado con un calefactor complementario:
Mixed unit with heat pump:	Apparecchio misto a pompa di calore:	Dispositif de chauffage mixte par pompe à chaleur:	Kombiheizgerät mit Wärmepumpe:	Calefactor combinado con bomba de calor:
Temperature application	Temperatura applicazione	Application à température	Temperatur Anwendung	Aplicación de temperatura
Water flow rate	Portata d'acqua	Débit fluide	Volumenstrom Wasser	Caudal agua
Outlet temperature	Temperatura di uscita	Température de sortie	Austrittstemperatur	Temperatura de salida
Parameters are declared for average/warmer/colder climate conditions	I parametri sono dichiarati per condizioni climatiche medie/ alte/ basse	Les paramètres sont déclarés pour les conditions climatiques moyennes/chaud/basse	Die Parameter sind für eine Mitteltemperaturanwendung anzugeben	Los parámetros se indicarán para condiciones climáticas medias/ alta/ baja
Rated heat output at Tdesignh	Potenza termica nominale a Tdesign	Puissance thermique nominale Tdesign	Wärmenennleistung Tdesignh	Potencia calorífica nominal Tdesignh
Seasonal space heating energy efficiency	Efficienza energetica stagionale del riscaldamento d'ambiente	Efficacité énergétique saisonnière pour le chauffage des locaux	Jahreszeitbedingte Raumheizungs-Energieeffizienz	Eficiencia energética estacional de calefacción
Seasonal space heating energy efficiency class	Classe di efficienza energetica stagionale del riscaldamento d'ambiente	Efficacité énergétique saisonnière pour le chauffage des locaux	Jahreszeitbedingte Raumheizungs-Energieeffizienz	Eficiencia energética estacional de calefacción
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj	Capacità di riscaldamento dichiarata a carico parziale, con temperatura interna pari a 20 °C e temperatura esterna Tj	Puissance calorifique déclarée à charge partielle pour une température intérieure de 20 °C et une température extérieure Tj	Angegebene Leistung für Teillast bei Raumlufttemperatur 20 °C und Außenlufttemperatur Tj	Capacidad de calefacción declarada para una carga parcial a una temperatura interior de 20 °C y una temperatura exterior Tj
Declared capacity for heating with outdoor temperature Tj = - 7 °C	Capacità di riscaldamento con temperatura esterna Tj = - 7 °C	Puissance calorifique déclarée avec la température extérieure Tj = - 7 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = - 7 °C	Capacidad de calefacción para una temperatura exterior Tj = - 7 °C
Declared capacity for heating with outdoor temperature Tj = +2 °C	Capacità di riscaldamento con temperatura esterna Tj = + 2 °C	Puissance calorifique déclarée avec la température extérieure Tj = + 2 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = + 2 °C	Capacidad de calefacción para una temperatura exterior Tj = + 2 °C
Declared capacity for heating with outdoor temperature Tj = + 7 °C	Capacità di riscaldamento con temperatura esterna Tj = + 7 °C	Puissance calorifique déclarée avec la température extérieure Tj = + 7 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = + 7 °C	Capacidad de calefacción para una temperatura exterior Tj = + 7 °C
Declared capacity for heating with outdoor temperature Tj = + 12 °C	Capacità di riscaldamento con temperatura esterna Tj = + 12 °C	Puissance calorifique déclarée avec la température extérieure Tj = + 12 °C	Erklärt, Raumheizung mit Außenlufttemperatur Tj = + 12 °C	Capacidad de calefacción para una temperatura exterior Tj = + 12 °C
Declared capacity for heating with outdoor temperature Tj = Bivalent temperature	Capacità di riscaldamento con temperatura esterna Tj = temperatura bivalente	Puissance calorifique déclarée avec la température extérieure Tj = Température bivalente	Erklärt, Raumheizung mit Außenlufttemperatur Tj = Bivalenttemperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura bivalente
Declared capacity for heating with outdoor temperature Tj = Operation limit temperature	Capacità di riscaldamento con temperatura esterna Tj = temperatura limite di esercizio	Puissance calorifique déclarée avec la température extérieure Tj = Température maximale de service	Erklärt, Raumheizung mit Außenlufttemperatur Tj = Betriebsgrenzwert-Temperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura limite de funcionamiento
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Per le pompe di calore aria/ acqua: Tj = - 15 °C (se TOL < - 20 °C)	Pour les pompes à chaleur air-eau: Tj = - 15 °C (si TOL < - 20 °C)	Für Luft-Wasser-Wärmepumpen: Tj = - 15 °C (wenn TOL < - 20 °C)	Para bombas de calor aire-agua: Tj = - 15 °C (si TOL < - 20 °C)
Bivalent temperature	Temperatura bivalente	Température bivalente	Bivalenttemperatur	Temperatura bivalente
Degradation coefficient	Coefficiente di degradazione	Coefficient de dégradation	Minderungsfaktor	Coefficiente de degradación
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj	Coefficiente di prestazione dichiarato o indice di energia primaria per carico parziale, con temperatura interna pari a 20 °C e temperatura esterna Tj	Coefficient de performance déclaré ou coefficient sur énergie primaire déclaré à charge partielle pour une température intérieure de 20 °C et une température extérieure Tj	Angegebene Leistungszahl oder Heizzahl für Teillast bei Raumlufttemperatur 20 °C und Außenlufttemperatur Tj	Coefficiente de rendimiento declarado o factor energético primario para una carga parcial a una temperatura interior de 20 °C y una temperatura exterior Tj
Declared coefficient of performance with outdoor temperature Tj = - 7 °C	Coefficiente di prestazione con temperatura esterna Tj = - 7 °C	Coefficient de performance déclaré avec la température extérieure Tj = - 7 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = - 7 °C	Capacidad de calefacción para una temperatura exterior Tj = - 7 °C
Declared coefficient of performance with outdoor temperature Tj = + 2 °C	Coefficiente di prestazione con temperatura esterna Tj = + 2 °C	Coefficient de performance déclaré avec la température extérieure Tj = + 2 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = + 2 °C	Capacidad de calefacción para una temperatura exterior Tj = + 2 °C
Declared coefficient of performance with outdoor temperature Tj = + 7 °C	Coefficiente di prestazione con temperatura esterna Tj = + 7 °C	Coefficient de performance déclaré avec la température extérieure Tj = + 7 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = + 7 °C	Capacidad de calefacción para una temperatura exterior Tj = + 7 °C
Declared coefficient of performance with outdoor temperature Tj = + 12 °C	Coefficiente di prestazione con temperatura esterna Tj = + 12 °C	Coefficient de performance déclaré avec la température extérieure Tj = + 12 °C	Erklärten Leistungszahl bei Außenlufttemperatur Tj = + 12 °C	Capacidad de calefacción para una temperatura exterior Tj = + 12 °C

ENGLISH	ITALIANO	FRANCAISE	DEUTSCH	ESPAÑOL
Declared coefficient of	Coefficiente di prestazione con	Coefficient de performance	Erklärten Leistungszahl bei	Capacidad de calefacción para
Declared coefficient of performance with outdoor temperature Tj = Operation limit temperature	Coefficiente di prestazione con temperatura esterna Tj = temperatura limite di esercizio	Coefficient de performance déclaré avec la température extérieure Tj = Température maximale de service	Erklärten Leistungszahl bei Außenlufttemperatur Tj = Betriebsgrenzwert-Temperatur	Capacidad de calefacción para una temperatura exterior Tj = Temperatura límite de funcionamiento
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Per le pompe di calore aria/acqua: Tj = - 15 °C (se TOL < - 20 °C)	Pour les pompes à chaleur air-eau: Tj = - 15 °C (si TOL < - 20 °C)	Für Luft-Wasser-Wärmepumpen: Tj = - 15 °C (wenn TOL < - 20 °C)	Para bombas de calor aire-agua: Tj = - 15 °C (si TOL < - 20 °C)
For air-to-water HP : Operation limit temperature	Per le pompe di calore aria/acqua: temperatura limite di esercizio	Pour les pompes à chaleur air-eau: Température limite de fonctionnement	Für Luft-Wasser-Wärmepumpen: Betriebsgrenzwert-Temperatur	Para bombas de calor aire-agua: Temperatura límite de funcionamiento
Heating water operating limit temperature	Temperatura limite di esercizio di riscaldamento dell'acqua	Température maximale de service de l'eau de chauffage	Grenzwert der Betriebstemperatur des Heizwassers	Temperatura límite de calentamiento de agua
Power consumption in modes other than active mode	Consumo energetico in modi diversi dal modo attivo	Consommation d'électricité dans les modes autres que le mode actif	Stromverbrauch in anderen Betriebsarten als dem Betriebszustand	Consumo de electricidad en modos distintos del activo
Off mode	Modo spento	Mode arrêt	Aus-Zustand	Modo desactivado
Thermostat-off mode	Modo termostato spento	Mode arrêt par thermostat	Thermostat-aus-Zustand	Modo desactivado por termostato
Standby mode	Modo stand-by	Mode veille	Bereitschaftszustand	Modo de espera
Crankcase heater mode	Modo riscaldamento del carter	Mode résistance de carter active	Betriebszustand mit Kurbelgehäuseheizung	Modo riscaldamento del carter
Supplementary heater	Riscaldatore supplementare	Dispositif de chauffage d'appoint	Zusatzheizgerät	Calefactor complementario
Nominal heating capacity	Potenza termica nominale	Puissance thermique nominale	Heizleistung nominal	Potencia térmica nominal
Other items	Altri elementi	Autres caractéristiques	Sonstige Elemente	Otros elementos
Capacity control	Controllo della capacità	Régulation de la puissance	Leistungssteuerung	Control de capacidad
Sound power level, indoors	Livello della potenza sonora, all'interno	Niveau de puissance acoustique, à l'intérieur	Schalleistungspegel, innen	Nivel de potencia acústica (interior)
Sound power level, outdoors	Livello della potenza sonora, all'esterno	Niveau de puissance acoustique, à l'extérieur	Schalleistungspegel, außen	Nivel de potencia acústica (exterior)
Annual electricity consumption for heating	Consumo di elettricità annuale per il riscaldamento	Consommation annuelle d'électricité pour le chauffage	Jahresstromverbrauch für die Heizung	Consumo anual de electricidad para la calefacción
Outdoor heat exchanger	Scambiatore di calore esterno	Echangeur de chaleur externe	Wärmetauscher äußere	Intercambiador de calor (exterior)
For air-to-water HP: Rated air flow rate, outdoors	Per le pompe di calore aria/acqua: portata d'aria, all'esterno	Pour les pompes à chaleur air-eau: débit d'air nominal, à l'extérieur	Für Luft-Wasser-Wärmepumpen: Nenn-Luftdurchsatz, außen	Para bombas de calor aire-agua: Caudal de aire nominal (exterior)
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	Per le pompe di calore acqua/acqua e salamoia/acqua: flusso di salamoia o acqua nominale, scambiatore di calore all'esterno	Pour les pompes à chaleur eau-eau ou eau glycolée-eau: débit nominal d'eau glycolée ou d'eau, échangeur thermique extérieur	Für Wasser/Sole-Wasser-Wärmepumpen/ Wasser- oder Sole-Nenndurchsatz	Para bombas de calor agua/salmuera a agua: Caudal de salmuera o de agua nominal, intercambiador de calor de exterior
Notes:	Note:	Remarques:	Hinweise:	Notas:
The parameters are declared for application at medium temperature, except in the case of low temperature heat pumps. For low temperature heat pumps, the parameters are declared for application at low temperature.	I parametri sono dichiarati per l'applicazione a temperatura media, tranne per le pompe di calore a bassa temperatura. Per le pompe di calore a bassa temperatura, i parametri sono dichiarati per l'applicazione a bassa temperatura.	Les paramètres sont déclarés pour l'application à moyenne température, excepté pour les pompes à chaleur basse température. Pour les pompes à chaleur basse température, les paramètres sont déclarés pour l'application à basse température.	Die Parameter sind für eine Mitteltemperaturanwendung anzugeben, außer für Niedertemperatur-Wärmepumpen. Für Niedertemperatur-Wärmepumpen sind die Parameter für eine Niedertemperaturanwendung anzugeben.	Los parámetros se declararán para aplicaciones de media temperatura, excepto si se trata de bombas de calor de baja temperatura. En el caso de las bombas de calor de baja temperatura, los parámetros se declararán para aplicaciones de baja temperatura.
Unit in standard configuration/execution, without optional accessories.	Unità in configurazione ed esecuzione standard, priva di accessori opzionali.	Unité en configuration et exécution standard, sans accessoires optionnels.	Gerät mit Standard-Konfiguration und -Ausführung, ohne wunschweises Zubehör.	Unidad en configuración y ejecución estándar, sin accesorios opcionales.



for a greener tomorrow

Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.



MITSUBISHI ELECTRIC HYDRONICS & IT COOLING SYSTEMS S.p.A.

Head Office: Via Sarson 57/c - 36061 Bassano del Grappa (VI) - Italy

Tel (+39) 0424 509 500 - Fax (+39) 0424 509 509

www.climaveneta.com

www.melcohit.com