

NEMO A: Motoevaporating units for indoor installation, equipped with scroll compressor and plate heat exchangers
Cooling Capacity: $5,4 \div 26,0$ kW



MAIN FEATURES

- Motoevaporating unit.
- 13 models available, for a wide selection opportunity.
- Average step of 2,5kW.
- EER up to 3,02.
- Scroll compressor.
- R410A Refrigerant charge.
- Single refrigerant circuit.
- Plate type heat exchanger.
- Suitable for indoor installation.

MAIN BENEFITS

- Availability of partial heat recovery system.
- Availability of kit for the reduction of the noise.
- Availability of remote condensers with axial fans (TEAM MATE series) and with plug fan (TEAM MATE PF series).
- Easily of maintenance.
- Eurovent Certification.

INDOOR INSTALLATION

The machines are designed for indoor installation.

REMOTE CONDENSER

The units are designed to be matched with remote condensers with axial fans (TEAM MATE series) or plug-fan (TEAM MATE PF series).

COMPLETENESS OF EQUIPMENT AND OPTIONAL

The units are standardly equipped with 3-speed water pump. On request is possible to install the system for the domestic hot water production and a chilled water tank.

WORKING LIMITS IN COOLING MODE

Evaporator chilled water outlet temperature: $-12 \div 20^{\circ}\text{C}$
Ambient temperature: $-10 \div 45^{\circ}\text{C}$



MAIN COMPONENTS

FRAMEWORK

- Base, self supporting frame and panelling in steel plate with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders.
- Colour: RAL 9002
- Insulation of the internal framework.

COMPRESSOR

- Orbiting spiral (SCROLL) hermetic compressors with spiral profile optimized for R410A refrigerant.
- ON / OFF capacity control (0 / 100%).
- Crankcase heater.
- Electric motor thermal protection via internal winding temperature sensors.
- Rubber supports.
- Electric motor:
 - Version M: single-phase electric motor with direct on line starting.
 - Version T: 2-pole 3-phase electric motor with direct on line starting.
- Phase sequence electronic relay.

EVAPORATOR

- Copper brazed plate type with cover plates, plates and connections in AISI 316 stainless steel.
- Anticondensate insulation made of polyurethane.
- Temperature sensors on water inlet and outlet.
- Differential water pressure switch for water flow control.
- 3-speed circulation pump.

REFRIGERANT CIRCUIT

- Thermostatic expansion valve.
- Service valves on liquid line and gas discharge.
- Pressure transducers with indication, control and protection functions, on low and high refrigerant pressure.
- 0÷10V proportional signal to manage the condensing control system of the remote air cooled condenser.
- High pressure safety switch with manual reset.
- Refrigerant circuit with copper tubing with anticondensate insulation of the suction line.
- Plastic capillary hoses for pressure sensors connection.
- R410A refrigerant charge.

ELECTRICAL PANEL

In accordance with EN60204-1 norms, suitable for indoor installation complete with:

- Main switch.
- Magnetothermic switch or fuses for compressor.
- Contactor for compressor.
- Transformer for auxiliary circuit and microprocessor supply.
- Panel with machine controls.
- Power supply:
 - M: 230/3/50
 - T: 400/3/50+N

CONTROL SYSTEM

- Microprocessor control. The system includes:
 - Display for the visualization of the alarm codes, set values and temperature values.
 - Dynamic set point.
 - Compressor running hour meter.
 - Contact for general alarm remotization.
 - "Low Temperature" set for operation with ambient air temperature up to -10°C.

HYDRAULIC CONNECTIONS OF HEAT EXCHANGERS

- The heat exchangers' threaded hydraulic connections correspond to ISO 228/1 – G M

TO BE MATCHED WITH REMOTE CONDENSER

The units are designed to be matched with remote condensers with axial fans (TEAM MATE series) or plug-fan (TEAM MATE PF series).



TEAM MATE

pg:193



TEAM MATE PF

pg:197

OPTIONAL ACCESSORIES

NEMO A MODEL	M 06 P1 J3	M 08 P1 J3	M 10 P1 J3	M 13 P1 J3	T 06 P1 J3	T 08 P1 J3	T 10 P1 J3	T 13 P1 J3	T 15 P1 J3	T 17 P1 J3	T 20 P1 J3	T 25 P1 J3	T 30 P1 J3
TEAM MATE remote condensers	•	•	•	•	•	•	•	•	•	•	•	•	•
TEAM MATE PF remote condensers	•	•	•	•	•	•	•	•	•	•	•	•	•
450 - Desuperheater	•	•	•	•	•	•	•	•	•	•	•	•	•
610 - Noise deadening cup on compressor	•	•	•	•	•	•	•	•	•	•	•	•	•
764 - Water tank	•	•	•	•	•	•	•	•	•	•	•	•	•
117 - Low water temperature set	•	•	•	•	•	•	•	•	•	•	•	•	•
920 - Remote control kit	•	•	•	•	•	•	•	•	•	•	•	•	•
923 - RC-Com MBUS/JBUS Serial board	•	•	•	•	•	•	•	•	•	•	•	•	•
889 - Master plant SEQUENCER	•	•	•	•	•	•	•	•	•	•	•	•	•
962 - Kit modem GSM	•	•	•	•	•	•	•	•	•	•	•	•	•
957 - Plantwatch without modem	•	•	•	•	•	•	•	•	•	•	•	•	•
930 - Remote graphic terminal kit	•	•	•	•	•	•	•	•	•	•	•	•	•

• available accessory; - not available accessory

TECHNICAL DATA NEMO A

NEMO A SIZE		M 06 P1 J3	M 08 P1 J3	M 10 P1 J3	M 13 P1 J3	T 06 P1 J3	T 08 P1 J3	T 10 P1 J3	T 13 P1 J3		
STANDARD	Cooling capacity (1)	kW	5,4	7,1	9,2	12,1	5,4	6,9	9,2	12,0	
	Unit power input (*)	kW	2,0	2,7	3,5	4,2	2,0	2,6	3,3	4,4	
	Evaporator water flow rate	m³/h	0,9	1,2	1,6	2,1	0,9	1,2	1,6	2,1	
	Evaporator pressure drop	kPa	31	21	28	23	31	20	28	23	
	Compressors		scroll	scroll	scroll	scroll	scroll	scroll	scroll	scroll	
	Quantity	n.	1	1	1	1	1	1	1	1	
	Capacity steps	n.	1	1	1	1	1	1	1	1	
	Pumping group										
	3-speed water pump	kW	0,4	0,4	0,4	0,4	0,4	0,4	0,4	0,4	
	Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
	Total refrigerant charge (optional excluded)	kg	4,7	4,8	5,1	5,4	4,7	4,8	5,1	5,4	
	Gas circuits	n.	1	1	1	1	1	1	1	1	
	Power supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	400/3/50+N	400/3/50+N	400/3/50+N	400/3/50+N	
	Max unit operating current (FLA) (*)	A	14,8	19,1	23,0	33,0	6,7	8,5	10,0	12,3	
	Unit starting current (LRA)	A	60,0	67,0	98,0	115,5	28,0	38,0	43,0	51,5	
	EER (1) (*)	kW/kW	2,67	2,61	2,66	2,85	2,67	2,65	2,75	2,76	
	Sound power level [Lw] (2)	dB(A)	56,2	56,2	58,2	58,2	56,2	56,2	58,2	58,2	
	Average sound pressure level [Lp _m] (3)	dB(A)	42,0	42,0	44,0	44,0	42,0	42,0	44,0	44,0	
	Net weight	kg	51,0	51,0	54,5	66,0	51,0	51,0	54,5	66,0	
	Hydraulic connections										
Evaporator IN/OUT - ISO228/1-G M	Ø	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"		
Refrigerant connection											
Liquid return	n x Ø	10	10	10	12	10	10	10	12		
Gas delivery	n x Ø	10	10	10	12	10	10	10	12		
TEAM MATE	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	1	1		
	Series TEAM MATE STD	Mod.	M 11	M 11	M 14	M 17	M 11	M 11	M 14	M 17	
	Nominal power in/out	kW	0,3	0,3	0,3	0,3	0,3	0,3	0,3	0,3	
	Max operating current	A	1,2	1,2	1,2	1,2	1,2	1,2	1,2	1,2	
	Power supply (**)	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
OPT	Partial heat recovery - Heating Capacity (4)	kW	2,0	2,6	3,4	4,4	2,0	2,5	3,4	4,4	
	Water tank - volume	l	40	40	40	40	40	40	40	40	
TEAM MATE LNO	NEMO A + TEAM MATE LNO										
	Cooling capacity (1)	kW	5,4	7,0	9,0	12,1	5,3	6,8	9,0	12,1	
	Unit power input	kW	1,7	2,4	3,2	3,8	1,7	2,3	3,1	4,0	
	EER (1) (*)	kW/kW	2,86	2,68	2,67	2,90	2,86	2,74	2,76	2,83	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	1	1	1	
	Series TEAM MATE LNO	Mod.	M 11	M 11	M 14	M 20	M 11	M 11	M 14	M 20	
	Nominal power in/out	kW	0,2	0,2	0,2	0,3	0,2	0,2	0,2	0,3	
	Power supply (**)	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
	TEAM MATE ELN	NEMO A + TEAM MATE ELN									
		Cooling capacity (1)	kW	5,3	6,8	8,7	11,7	5,3	6,6	8,7	11,7
Unit power input		kW	1,7	2,5	3,3	4,0	1,7	2,4	3,2	4,1	
EER (1) (*)		kW/kW	2,77	2,54	2,50	2,73	2,78	2,61	2,59	2,65	
REMOTE CONDENSER - Quantity		n.	1	1	1	1	1	1	1	1	
Series TEAM MATE ELN		Mod.	M 11	M 11	M 14	M 20	M 11	M 11	M 14	M 20	
Nominal power in/out		kW	0,2	0,2	0,2	0,3	0,2	0,2	0,2	0,3	
Power supply (**)		V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
TEAM MATE PF STD		NEMO A + TEAM MATE PF STD									
		Cooling capacity (1)	kW	5,4	7,1	8,8	11,7	5,4	6,9	8,9	10,9
	Unit power input	kW	1,6	2,3	3,3	4,0	1,6	2,2	3,1	4,6	
	EER (1) (*)	kW/kW	2,69	2,63	2,43	2,62	2,70	2,67	2,52	2,17	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	1	1	1	
	Series TEAM MATE PF STD	Mod.	T 11	T 11	T 11	T 14	T 11	T 11	T 11	T 11	
	External static pressure	Pa	50	50	50	50	50	50	50	50	
Nominal power in/out	kW	0,4	0,4	0,4	0,4	0,4	0,4	0,4	0,4		
Power supply (**)	V/Ph/Hz	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60		
TEAM MATE PF LNO	NEMO A + TEAM MATE PF LNO										
	Cooling capacity (1)	kW	5,5	7,3	9,1	11,8	5,5	7,1	9,1	11,8	
	Unit power input	kW	1,6	2,2	3,1	4,0	1,6	2,1	3,0	4,1	
	EER (1) (*)	kW/kW	2,96	2,90	2,69	2,74	2,97	2,93	2,79	2,67	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	1	1	1	
	Series TEAM MATE PF LNO	Mod.	T 14	T 14	T 14	T 17	T 14	T 14	T 14	T 17	
	External static pressure	Pa	36	36	36	36	36	36	36	36	
Nominal power in/out	kW	0,3	0,3	0,3	0,3	0,3	0,3	0,3	0,3		
Power supply (**)	V/Ph/Hz	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60		
TEAM MATE PF ELN	NEMO A + TEAM MATE PF ELN										
	Cooling capacity (1)	kW	5,4	7,1	8,9	11,4	5,4	6,9	8,9	11,4	
	Unit power input	kW	1,6	2,3	3,2	4,2	1,6	2,2	3,1	4,4	
	EER (1) (*)	kW/kW	3,03	2,87	2,60	2,59	3,04	2,92	2,68	2,51	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	1	1	1	
	Series TEAM MATE PF ELN	Mod.	T 14	T 14	T 14	T 17	T 14	T 14	T 14	T 17	
	External static pressure	Pa	25	25	25	25	25	25	25	25	
Nominal power in/out	kW	0,2	0,2	0,2	0,2	0,2	0,2	0,2	0,2		
Power supply (**)	V/Ph/Hz	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60		

1. Referred to chilled water temperature 12/7°C; ambient temperature 35°C.
 2. Sound power level [Lw] according to ISO EN 9614 - 2
 3. Average sound pressure level [Lp_m] 1m far according to ISO EN 3744.
 4. Referred to chilled water temperature 12/7°C; ambient temperature 35°C and recovery hot water temperature 40/45°C.
- (*) The value includes the remote condenser
(**) The remote condenser has separated power supply

TECHNICAL DATA NEMO A

NEMO A SIZE		T 15 P1 J3	T 17 P1 J3	T 20 P1 J3	T 25 P1 J3	T 30 P1 J3		
STANDARD	Cooling capacity (1)	kW	13,6	16,2	17,7	21,5	26,0	
	Unit power input (*)	kW	4,7	5,4	6,3	7,4	8,8	
	Evaporator water flow rate	m³/h	2,3	2,8	3,0	3,7	4,5	
	Evaporator pressure drop	kPa	30	25	30	32	29	
	Compressors		scroll	scroll	scroll	scroll	scroll	
	Quantity	n.	1	1	1	1	1	
	Capacity steps	n.	1	1	1	1	1	
	Pumping group							
	3-speed water pump	kW	0,4	0,4	0,4	0,4	0,4	
	Refrigerant		R410A	R410A	R410A	R410A	R410A	
	Total refrigerant charge (optional excluded)	kg	5,4	5,8	5,8	6,5	7,1	
	Gas circuits	n.	1	1	1	1	1	
	Power supply	V/Ph/Hz	400/3/50+N	400/3/50+N	400/3/50+N	400/3/50+N	400/3/50+N	
	Max unit operating current (FLA) (*)	A	13,8	17,0	17,0	23,0	24,0	
	Unit starting current (LRA)	A	64,0	75,0	101,0	111,0	118,0	
	EER (1) (*)	kW/kW	2,88	3,02	2,81	2,91	2,97	
	Sound power level [Lw] (2)	dB(A)	61,2	65,2	62,2	64,2	64,2	
Average sound pressure level [Lp _m] (3)	dB(A)	47,0	51,0	48,0	50,0	50,0		
Net weight	kg	72,0	102,0	102,0	111,0	120,0		
Hydraulic connections								
Evaporator IN/OUT - ISO228/1-G M	Ø	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"		
Refrigerant connection								
Liquid return	n x Ø	12	12	12	16	16		
Gas delivery	n x Ø	12	12	12	16	16		
TEAM MATE	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	
	Series TEAM MATE STD	Mod.	M 20	M 25	M 25	M 30	M 35	
	Nominal power in/out	kW	0,4	0,5	0,5	0,5	0,5	
	Max operating current	A	1,8	2,9	2,9	2,9	2,9	
	Power supply (**)	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
OPT	Partial heat recovery - Heating Capacity (4)	kW	5,0	5,9	6,5	7,9	9,6	
	Water tank - volume	l	40	40	40	40	40	
TEAM MATE LNO	NEMO A + TEAM MATE LNO							
	Cooling capacity (1)	kW	13,8	16,6	18,2	22,4	26,6	
	Unit power input	kW	4,2	4,8	5,6	6,6	8,1	
	EER (1) (*)	kW/kW	2,94	3,19	2,99	3,10	3,05	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	
	Series TEAM MATE LNO	Mod.	M 25	M 30	M 30	M 45	M 45	
	Nominal power in/out	kW	0,5	0,5	0,5	0,7	0,7	
	Power supply (**)	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
	TEAM MATE ELN	NEMO A + TEAM MATE ELN						
		Cooling capacity (1)	kW	13,4	16,3	17,7	21,9	25,8
Unit power input		kW	4,4	4,9	5,9	6,8	8,5	
EER (1) (*)		kW/kW	2,82	3,08	2,84	2,97	2,87	
REMOTE CONDENSER - Quantity		n.	1	1	1	1	1	
Series TEAM MATE ELN		Mod.	M 25	M 30	M 30	M 45	M 45	
Nominal power in/out		kW	0,4	0,4	0,4	0,6	0,6	
Power supply (**)		V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	
TEAM MATE PF STD		NEMO A + TEAM MATE PF STD						
		Cooling capacity (1)	kW	13,3	15,8	17,7	21,8	25,7
	Unit power input	kW	4,5	5,1	5,9	6,9	8,5	
	EER (1) (*)	kW/kW	2,71	2,79	2,72	2,67	2,62	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	
	Series TEAM MATE PF STD	Mod.	T 17	T 21	T 24	T 33	T 33	
	External static pressure	Pa	50	50	50	50	50	
	Nominal power in/out	kW	0,5	0,5	0,6	1,3	1,3	
Power supply (**)	V/Ph/Hz	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60		
TEAM MATE PF LNO	NEMO A + TEAM MATE PF LNO							
	Cooling capacity (1)	kW	13,4	15,9	18,4	21,8	25,7	
	Unit power input	kW	4,4	5,1	5,5	6,9	8,5	
	EER (1) (*)	kW/kW	2,82	2,88	2,90	2,87	2,78	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	
	Series TEAM MATE PF LNO	Mod.	T 21	T 24	T 33	T 38	T 38	
	External static pressure	Pa	36	36	36	36	36	
	Nominal power in/out	kW	0,3	0,4	0,8	0,7	0,7	
Power supply (**)	V/Ph/Hz	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60		
TEAM MATE PF ELN	NEMO A + TEAM MATE PF ELN							
	Cooling capacity (1)	kW	12,9	15,4	17,9	21,2	24,8	
	Unit power input	kW	4,6	5,4	5,8	7,2	9,0	
	EER (1) (*)	kW/kW	2,66	2,73	2,85	2,77	2,62	
	REMOTE CONDENSER - Quantity	n.	1	1	1	1	1	
	Series TEAM MATE PF ELN	Mod.	T 21	T 24	T 33	T 38	T 38	
	External static pressure	Pa	25	25	25	25	25	
	Nominal power in/out	kW	0,2	0,3	0,5	0,5	0,5	
Power supply (**)	V/Ph/Hz	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60	380-480/3/50-60		

1. Referred to chilled water temperature 12/7°C; ambient temperature 35°C.

2. Sound power level [Lw] according to ISO EN 9614 - 2

3. Average sound pressure level [Lp_m] 1m far according to ISO EN 3744.

4. Referred to chilled water temperature 12/7°C; ambient temperature 35°C and recovery hot water temperature 40/45°C.

(*) The value includes the remote condenser

(**) The remote condenser has separated power supply

DIMENSIONS (mm)

